

FLAT INLAY
BUTTON
SO THEY
DON'T
GET
RUBBED

ANTHRO
TESTING
REQUIRED

BUTTON
LAYOUT

2 SWITCHES

SHALLER
DISPUSER
CONE

REFLECTIVE IF POSSIBLE
- POLARIZED

INCLUDE
EXPOSURE
EV +/- METER
MAYBE PHYSICAL
LIGHTS

LIGHT INDICATOR
ON OFF STATUS
FLASHING OF EV
LIGHTS

LENS SHOULD BE
SLIGHTLY ABOVE
SHUTTER TO AVOID OBSCURE

SHALLER PADDLE

EYEDIEZ
SILHOUETTE

WIDER

INCORPORATE WOODEN
ELEMENT?

"SHUTTER"

ESTABLISH MARGINS
PROPORTIONING

5:4?

HARD
PRESS
BUTTONS

MEAN
HANDHELD
LENGTH

7.5" MAN
16.9" WOMAN
7.1" AVG

RECESSED
DIFFUSERS

NOT FEELING EXTRUDER INDICATOR
VIEWFINDER, USE
OF NEGATIVE SPACE

LEFT AS
NEGATIVE
SPACE

MORE
CURVES AGAINST
SQUARE
EDGES

LOOK AT LE
HANDS

ONE HANDED OPERATION
LAYOUT

FILLET
INSIDE
LEDGE

-CONNECTS

INSET

TAKE FROM
CAMERA

*LIGHTMETER / SOME SORT
OF MULTI
METER APPARATUS

*CREATIVITY

*COLOR METER DIALS

*SOUND RECORDER AND
SWITCH

*THINKING ABOUT ECONOMY
AND
FUNCTION
FOR TEENAGE
ENGINEERS

*SPACED ALUMINUM

*INFLUENCE FROM DIGITAL
TAPE RECORDER AND
HOTSHOE LIGHT METERS

*HIGH TACTILE VALUE

ADD HOLLOW
GRIP

FOLDOUT
HANDLE

ADD HOLLOW
GRIP

FOLDOUT
HANDLE

UP
DOWN
SEL.
BACK

CLICK IN
TO ROLL
HANDLE
OUT

NEAR
DIFFUSION
BULBS

FLIPOUT HANDLE
OR NO

IX "SS DIAL"

IX BUTTONS CORRESPOND
TO FUNCTION
IX PADDLE HANDLE

SPACE
SCREEN
68

TP-DIMENSIONS
96x68x16

RETAIN 68MM

WHITE
RAISED

HANDLE
HANDHELD

RIM EDGE
LOOK AT
IPHONE 13
CAMERA SYSTEM

ITNEY

*FINALIZE
BUTTON/SW

*BUTTON CH

*SCREEN CH

*HANDLE IN

LAMINA

BACK
PADDING

BRAN

WITHOUT CONTROLS AS
HANDLE

OFFSET
BY 1-3MM
SAME INNER
DIAMETER

REFLECTIVE
@ 16MM DIA

4
2
16