

I'm human



Monowave 300 user guide filetype pdf

We use cookies on our website, including some necessary ones (like the shopping cart) and others that help us improve your experience with analysis, media, and marketing services. We also use third-party cookies from companies like Google or Facebook if you've given us permission to do so. However, keep in mind that your data might be transferred to the USA, which has different data protection laws than ours. This could potentially allow US authorities to access your data for surveillance purposes. You can either accept all cookies with a single click or go into our cookie settings and customize them to suit your preferences. If you decline all cookies, we'll only use those that are absolutely necessary. You also have the option to withdraw your consent at any later time by adjusting your cookie settings. High-speed reactions require precise control over safety features to ensure productivity and purity across various applications. Reusing vials, caps, and septa reduces consumable costs and minimizes the environmental footprint in research laboratories. The Monowave reactor offers a world of microwave synthesis with optimized reaction conditions and over 1000 successfully performed applications. It allows for 24 unattended reactions in sequence, saving time while increasing efficiency. High-density field production provides fast, uniform heating up to 300 °C, accompanied by powerful stirring at 1200 rpm for temperature homogeneity. The magnetron adjusts its power automatically, eliminating guesswork about sample absorption and ensuring high yields and clean reactions with maximum reproducibility. Temperature measurement via an IR sensor or optional fiber-optic ruby thermometer provides precise control over demanding reactions. Various vessels are available, including silicon carbide ones that efficiently absorb microwave energy while shielding the interior from radiation, allowing for solvent comparison across chemical reactions. The Monowave 400 and Monowave 450 offer digital camera capabilities to record images and videos of chemical reactions, with the Monowave 400 R combinable with Anton Paar's Cora 5001 Raman spectrometer for in-situ Raman spectroscopy measurements. This aids in identifying intermediates and short-lived transition states, further optimizing research outcomes. Reaction kinetics and reaction conditions optimization with real-time chemical composition data. The contactless measurement eliminates concerns about cross-contamination and cleaning between experiments. Monowave specifications: - Filling volume: 6 mL for 10 mL vial, 20 mL for 30 mL vial, or 2 mL for 4 mL vial. - Max operation pressure: Up to 30 bar (435 psi) or 20 bar (290 psi), with the option to upgrade. - IR and fiber-optic temperature max: Up to 300 °C, with optional upgrades to 260 °C. - Power consumption: 850 W. Vial materials: Borosilicate glass and silicon carbide. Cap material: PEEK. The system includes an integrated camera that can be upgraded for autosampling. Anton Paar provides extensive technical support through over 350 manufacturer-certified experts worldwide, ensuring local language assistance and protection of investments throughout their lifecycle, backed by a 3-year warranty.