

[Click Here](#)



## Mattress firm 300 adjustable base owner's manual

**Mattress firm 300 adjustable base manual. Mattress firm 300 remote control manual. Mattress firm 900 adjustable base manual. Mattress firm 50 series adjustable base manual. 300 adjustable base manual.**

Remove top of shipping carton and check contents for damage; read all instructions before use. Due to injury risk, two adults are required to handle and move the adjustable base. Cut zip-tie from electrical power supply and remove mattress retainer (set aside). Be cautious when using sharp instruments as injury is possible if tools aren't used properly. Carefully lift base head section out of carton and place on clean surface; remove divider and foot section, then slide them together to align mounting holes. Place T-Spacers between mounting points and insert carriage bolts through square holes in center support bracket. Hand tighten nuts using provided wrench. Route motor cables underneath the base frame and extend electrical power cord out the head end. Screw legs into threaded inserts at the corners of the base frame and adjust leg height by pushing pin to desired level. Rotate the base over onto its legs, remove remaining packaging, and install batteries in remote control. Lower the base to flat position and install mattress retainer at the foot end. Place the mattress on the base to complete assembly; refer to Troubleshooting section of owner's manual if issues arise. To register your adjustable base, visit or call Mattress Firm at 844-628-8376. Adjustable beds can be used with firm mattresses, but not all mattresses are compatible. Most memory foam, latex, and non-innerspring mattresses work well with adjustable beds. However, some disadvantages include higher costs, increased noise, extreme heaviness, restricted movement, and unique sizing categories. Faulty wiring or electrical issues can cause an adjustable bed to stop working. It's also possible that the bed's components need to be replaced under warranty. Adjustable beds can worsen back pain by not distributing forces properly. They require maintenance, but motors and gears are permanently lubricated. Loudness can be caused by a metal frame or supports, and noise can be reduced by minimizing contact points. To connect a mattress Firm 300 remote, press and hold the buttons for five seconds after flashing, then release and press again to connect. To disable child lock on an Base remote, press and hold FOOT UP and FOOT DOWN together for approximately three seconds until the backlight flashes twice. An adjustable bed can alleviate this by allowing you to adjust the height and position of the mattress. However, for safety reasons, you should not leave your adjustable bed in the upright position when it's not in use. Before assembling the base, make sure to follow the instructions carefully and have two adults assist you due to the risk of injury involved. Remove the packaging by removing the top shipping carton and verifying its contents. To assemble the base, lift the head section out of the carton and place it on a flat surface. Then remove the divider from the carton and attach the foot section to the head section while ensuring that the mounting holes are aligned. Make sure to handle sharp instruments with care as they can cause injury if not used properly. Always keep your hands and fingers clear when sliding the bases together. Once all hardware is installed, tighten the nuts using a provided wrench, but make sure to hand-tighten first. Route the electrical power cord underneath the base frame and connect it to the head motor cable. Finally, install the legs into the threaded inserts at the corners of the base frame and adjust their height by pushing a pin in, making sure the base is level on the floor. User manual for Mattress Firm's 300/60 K/CK sectional base, a PDF document providing instructions and guidelines.