



Vulcan Seals Type 196
22mm Grundfos®
Technical Data Sheet



Product Description

The Vulcan Seals Type 196 (22mm) is an elastomeric bellows seal with special profile boot-mounted stationaries to suit Grundfos® LM-, LP-, LPD, and LPE- series pumps. Suitable for a wide range of water transfer duties associated with building service vertical multistage pumps.

Why Choose the Vulcan Seals Type 196 22mm Grundfos®?
Featuring the design benefits of the Vulcan Seals Type 192B but with fitting dimensions suitable for the seal chambers of this pump range.

Pump Ranges

The Grundfos® pump model includes the following pump ranges: "LM-Series", "LP-Series", "LPD-Series"and "LPE-Series".


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Seal Code
EP	VCP1 Carbon	VSR1 Silicon Carbide	304 Stainless Steel	.E.D.
Viton™/FKM	VCP1 Carbon	VTN1 Tungsten Carbide	304 Stainless Steel	.V.E.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D3 (mm)	L1 (mm)	L2 (mm)
22.00	0220	37.00	36.00	33.00	12.00

Dimensions in mm
*Non-stock guarantee



© ™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.
** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.