

Phone: +44 (0) 114 249 3333

Email: contact@vulcanseals.com

Vulcan Seals Type 1689 IMO®

Technical Data Sheet



Product Description

The Vulcan Seals Type 1689 IMO® can suit I.M.O.® ACE Series positive displacement pumps of generation 3 or above, fitted with "T" or "Q" code shaft seals.

The Vulcan Seals Type 1689 IMO® offers both performance and handling benefits over the OEM design, owing to the standard rotary plus stationary design instead of the original multicomponent design that requires assembly on the shaft during installation.

The rotary part employs set screws to drive from the shaft the same as the original design, but the set screws can be readily accessed unlike the original.

The single-part stationary is also much easier to handle and install compared to the original. For ACE pumps with "U" or "V" code seals fitted, please use the Vulcan Seals Type 1690, and contact us for details on our alternative seals for ACE generation 1 or 2 pump models.

Why Choose the Vulcan Seals Type 1689 IMO®?

The Vulcan Seals Type 1689 IMO® can replace the five-part OEM seal supplied for ACE series pumps, generations 3 and above, we produce the following standard configuration seals with a rotary and a stationary, which are far easier to install than the original OEM seal:

- To replace OEM seal types "U" and "V" use the Vulcan Seals Type 1690
- To replace OEM seal types "T" and "Q" use the Vulcan Seals Type 1689

Pump Ranges

The IMO® pump model includes the following pump ranges: "ACE 025", "ACE 032" and "ACE 038" models of "K3", "L3" or "N3" generation or higher with "xQxx" or "xTxx" designation.


Standard Face Material Combinations

| Elastomers | Rotary Face | Stationary Face | Metals | Complete Seal Code |
|------------|----------------------|----------------------|---------------------|--------------------|
| Viton™/FKM | VSR1 Silicon Carbide | VSR1 Silicon Carbide | 304 Stainless Steel | .V.S. |

Dimensional Data

| DØ (Metric) | Seal Size Code | D1 (mm) | D3 (mm) | L1 (mm) | L2 (mm) |
|-------------|----------------|---------|---------|---------|---------|
| 22.00 | 0220 | 35.00 | 33.00 | 21.50 | 23.50 |

Dimensions in mm



^{*}Non-stock guarantee

^{® ™} All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.

^{**} All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.