



Vulcan Seals Type 24B
Technical Data Sheet



Product Description

The Vulcan Seals Type 24B is a resilient, rubber diaphragm mounted parallel spring seal design with self-adjusting head to accommodate minor shaft misalignment and run-out.

The seal drive is provided by the diaphragm bellows tightly gripping the shaft and providing positive drive to the seal head and sealing face. The Vulcan Seals diaphragm seal designs are bi-directional "pusher" seals that minimise shaft fretting as the spring is constantly providing energising force to the shaft contact point and sealing face.

Supplied with a Vulcan Seals Type 19B boot-mounted stationary for DIN24960/En12756 L1K seal chambers with shallow recesses.

Why Choose the Vulcan Seals Type 24B?

- Proficient diaphragm bellows design fully compliant to DIN24960/En12756 L1K dimensions to suit common European metric seal chambers.
- Boot mounted stationary provides maximum elastomer sealing contact to the housing surface.
- Base plate fitted at the spring drive end provides firm contact against a shaft step or circlip that sets the seal operating height. This component can be removed if not required.
- A widely utilised mechanical seal type highly suited to general light to medium duties and capable of long service life.

Standard Face Material Combinations

Rotary Face	Stationary Face	Complete Seal Code
VCP1 Carbon	VAW1 Ceramic	C
VCP1 Carbon	VSR1 Silicon Carbide	D
VSR1 Silicon Carbide	VAW1 Ceramic	G
VSR1 Silicon Carbide	VSR1 Silicon Carbide	S
VTN2* Tungsten Carbide	VTN1* Tungsten Carbide	H

Guaranteed Stock/Material Elastomers: Viton™/FKM, EP, Nitrile and Metallurgy 304SS
*Non-stock guarantee

Elastomer Temperature Capabilities

	Minimum	Maximum
Nitrile	-30°C	+120°C
EP	-40°C	+140°C
Viton™/FKM	-30°C	+180°C


Pressure: Up to 14 bar (203 psi)

Mechanical Seal Replacement Range

Vulcan Seals Type 24B is a dimensional replacement mechanical seal for the following seal ranges:

- Lidering® | Type 119 KU*
- Lidering® | Type LRB04*

*Rotary Face | **Stationary Face



Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D3 (mm)	L1 (mm)	L2 (mm)	L1K
12	0120	23.00	21.70	25.90	6.60	32.50
14	0140	25.00	24.40	28.40	6.60	35.00
16	0160	27.00	27.00	28.40	6.60	35.00
18	0180	33.00	30.60	30.00	7.50	37.50
20	0200	35.00	33.40	30.00	7.50	37.50
22	0220	37.00	33.40	30.00	7.50	37.50
24	0240	39.00	37.80	32.50	7.50	40.00
25	0250	40.00	39.20	32.50	7.50	40.00
28	0280	43.00	42.10	35.00	7.50	42.50
30	0300	45.00	44.00	35.00	7.50	42.50
32	0320	48.00	45.60	35.00	7.50	42.50
33	0330	48.00	45.60	35.00	7.50	42.50
35	0350	50.00	49.30	35.00	7.50	42.50
38	0380	56.00	52.70	36.00	9.00	45.00
40	0400	58.00	55.70	36.00	9.00	45.00
43	0430	61.00	58.60	36.00	9.00	45.00
45	0450	63.00	61.00	36.00	9.00	45.00
48	0480	66.00	64.00	36.00	9.00	45.00
50	0500	70.00	66.10	38.00	9.50	47.50
53	0530	73.00	70.60	36.50	11.00	47.50
55	0550	75.00	70.60	36.50	11.00	47.50
58*	0580	78.00	80.00	41.50	11.00	52.50
60	0600	80.00	80.00	41.50	11.00	52.50
63*	0630	83.00	82.10	41.50	11.00	52.50
65	0650	85.00	80.00	41.50	11.00	52.50
68*	0680	90.00	90.00	41.20	11.30	52.50
70	0700	92.00	90.00	48.70	11.30	60.00
75	0750	97.00	96.80	48.70	11.30	60.00
80	0800	105.00	104.00	48.00	12.00	60.00
85	0850	110.00	108.00	46.00	14.00	60.00
90	0900	115.00	111.00	51.00	14.00	65.00
95	0950	120.00	119.00	51.00	14.00	65.00
100	1000	125.00	124.00	51.00	14.00	65.00

Dimensions in mm and inches
*Non-stock guarantee




Maximum Operating Pressure

The PV Chart shows the maximum operating pressures of this Vulcan Seals type, based on the seal face materials used. Different lines on the chart indicate different material combinations, as shown underneath.

It also assumes stable operation in a clean, cool, lubricating and nonvolatile fluid with an adequate flush rate.

For more in-depth pressure rating calculations based on specific material combinations and application conditions, please consult us.

PV Chart



Application Conditions

	Criteria	Multiplier
Product Fluid	Lubricating fluids	X 1.00
	Aqueous solutions / Water	X 0.85
Temperature	Below 70°C (158°F)	X 1.00
	71°C to 120°C (160°F to 248°F)	X 0.85
	121°C to 175°C (250°F to 347°F)	X 0.75
	Over 176°C (349°F)	X 0.60
Speed	Up to 1750 rpm	X 1.00
	1750 to 3600 rpm	X 0.80

Face and Seat Materials

Combination	Multiplier
Carbon vs Ceramic	x 0.50
Carbon vs Silicon Carbide	x 1.00
Silicon Carbide vs Ceramic	x 0.35
Silicon Carbide vs Silicon Carbide	x 0.50
Tungsten Carbide vs Tungsten Carbide	x 0.50

Example Calculation for Vulcan Seals Type 24B

- A. Shaft size: 38mm therefore pressure is 13 bar (from PV Chart)
- B. Media: Water (multiplier = 0.85)
- C. Temperature: 50°C (multiplier = 1.00)
- D. Speed: 1450 rpm (multiplier = 1.00)
- E. Face combination: Carbon vs Silicon Carbide (multiplier = 1.00)

For this particular Vulcan Seals Type 24B seal size, the calculation for the approximate guidance maximum operating pressure would be:

A x B x C x D x E
13 bar x 0.85 x 1.00 x 1.00 x 1.00 = 11.05 bar

Guidance Only

Please note that due to the many operational and application variables that affect seal performance, the information given on this page is for guidance only.

We therefore strongly recommend careful individual testing and monitoring of all seals and related equipment for any proposed application.

Our policy is one of continuous technical and efficiency improvement. As such, all specifications may be subject to change without prior notice.

© TM All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.

** Important: These limits are the theoretical elastomer or design limitations. For maximum theoretical operating pressure for your specific size and application please refer to calculation example within this data sheet. All performance information given is for guidance only and is dependent on material, operating and application factors that affect seal performance.