



Vulcan Seals Type 1682

Alfa Laval®

Technical Data Sheet



Product Description

The Vulcan Seals Type 1682 Alfa Laval® 'O'-ring mounted wave spring seals are intended to suit the compact seal chambers of Alfa Laval® LKPL, "NMOG", "SR" and "SRU" series lobe rotor pumps when fitted with standard single "R90" OEM seals.

For pumps with hygienic non-flushed seal chambers, please see the Vulcan Seals Type 1680 Alfa Laval® datasheet, and for pumps with flushed seal chambers and double seals, please see the Vulcan Seals Type 1694 Alfa Laval® datasheet.

The Vulcan Seals Type 1682 Alfa Laval® is available with monolithic Carbon or Tungsten carbide stationaries as standard; if a steel stationary with an inserted Carbon face is preferred, please specify Vulcan Seals Type 1682A when ordering.

Why Choose the Vulcan Seals Type 1682 Alfa Laval®?

- For "SR" and "SRU" series pumps with flushed seal chambers and double seals, see Vulcan Seals Type 1694.
- For pumps with hygienic style "Hy-clean" single seals fitted, see Vulcan Seals Type 1680 above.

Pump Ranges

The Alfa Laval® pump model includes the following pump ranges: "LKPL", "NMOG", "SR" and "SRU" range models when fitted with "R90" single seals. Each pump requires two identical seals, one for each shaft.

Compliance & Certificates



Also available with built materials that adhere to the above compliance standards and certificates. Please enquire about your requirements.


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Seal Code
EPDM	304 Stainless Steel	VCP1 Carbon	304 Stainless Steel	.E.P.
Viton™/FKM	304 Stainless Steel	VCP1 Carbon	304 Stainless Steel	.V.P.
EPDM	VTN2 Tungsten Carbide	VTN1 Tungsten Carbide	304 Stainless Steel	.E.H.
Viton™/FKM	VTN2 Tungsten Carbide	VTN1 Tungsten Carbide	304 Stainless Steel	.V.H.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D3 (mm)	L1 (mm)	L2 (mm)	OEM Ref.
20.00	0200	30.00	32.40	20.00	10.50	SR 1
30.00	0300	41.30	44.00	21.40	11.10	SR 2
35.00	0350	46.95	50.80	22.00	12.00	SR 3
45.00	0450	58.26	62.40	22.90	12.60	SR 4
55.00	0550	69.55	76.00	29.30	13.20	SR 5
75.00	0750	92.15	99.20	31.10	14.40	SR 6

Dimensions in mm
*Non-stock guarantee



®™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.
** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.