



## Vulcan Seals Types 40S8

Grundfos®

Technical Data Sheet



### Product Description

Vulcan Seals Type 40S and Vulcan Seals 40S8 range 'O'-ring mounted robust multi-spring seals to suit the upper position in Grundfos® "S" series submersible pumps with the later generation style seals installed. The OEM older style seal is a conical single spring seal, please see the Vulcan Seals Type 81 data sheet for more details on the older style. These seals offer the design benefits of the Vulcan Seals Type 40, with short DIN-profile 'O'-ring stats of Vulcan Seals Type 8 or 24 range to suit the specific dimension requirements of this pump range. The Vulcan Seals Type 40S8 is the upper bearing position seal, please see the Vulcan Type 42 data sheet for the lower impeller position seal.

### Why Choose the Vulcan Seals Type 40S8 Grundfos®?

- 'O'-ring mounted multi-spring, balanced seals, specifically designed for Grundfos® "S" series submersible pumps; upper and lower positions.
- Vulcan Seals Type 40S8 is for the upper, oil bath position, and Vulcan Seals Type 42 with the distinctive stationary profile, is for the lower, impeller position.
- Vulcan Seals Type 42 (65mm) lower seal has a distinctive extended barrel with two 'O'-rings to seal inside the impeller recess, as per the original OEM seal.

### Pump Ranges

The Grundfos® pump model includes the following pump ranges: "S-Series" submersible pumps with the appropriate shaft size and seal type seals fitted.

### Compliance & Certificates



Also available with built materials that adhere to the above compliance standards and certificates. Please enquire about your requirements.

### Standard Face Material Combinations


Elastomers	Rotary Face	Stationary Face	Metals	Complete Seal Code
Viton™/FKM	VCD1 Carbon	VSR1 Silicon Carbide	316 Stainless Steel	.V.DS.

### Dimensional Data

D <sub>0</sub> (Metric)	Seal Size Code	Type Code	D <sub>1</sub> (mm)	D <sub>3</sub> (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)
38.00	0380	40S	56.00	53.00	34.00	11.00
50.00	0500	40S8	70.00	65.60	34.50	9.50
65.00	0650	40S8	85.00	84.20	36.50	11.00

Dimensions in mm

\*Non-stock guarantee



<sup>® TM</sup> All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.

\*\* All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.

**Embrace Excellence - Service | Quality | Value | Integrity**

Mechanical Seals | FEP/PFA Encapsulated 'O'-rings | Gland Packing | Expanded PTFE Gasketing  
UK/World: +44 (0) 114 249 3333 | USA: +1 952 955 8800 | [www.vulcanseals.com](http://www.vulcanseals.com) | [contact@vulcanseals.com](mailto:contact@vulcanseals.com)