



Vulcan Seals Type 215

Sulzer®

Technical Data Sheet



Product Description

The **Vulcan Seals Type 215 Sulzer®** parallel spring diaphragm bellows seals with specific design O-ring mounted stationaries (0200 size has a Vulcan Seals Type 19B boot stationary), intended to suit the seal chambers of former ABS® brand submersible pumps, such as "Jumbo J®" series.

The **Vulcan Seals Type 215 Sulzer®** seal will also interchange with elastomeric bellows seals found in recently produced Sulzer® brand "J" series submersible pumps.

Why Choose the Vulcan Seals Type 215 Sulzer®?

The **Vulcan Seals Type 215 Sulzer®** design seal will interchange with elastomeric bellows version seals sometimes found in recently produced "J series" pumps.

Pump Ranges

The Sulzer® (former ABS®) pump model includes the following pump ranges: "Jumbo" and "J®" models with relevant size seals fitted.

Compliance & Certificates



Also available with built materials that adhere to the above compliance standards and certificates. Please enquire about your requirements.

Standard Face Material Combinations

Elastomers		Rotary Face			Stationary Face			Metals		Complete Seal Code	
Nitrile		VSR1 Silicon Carbide			VSR1 Silicon Carbide			304 Stainless Steel		.N.S.	


Dimensional Data

D \varnothing (Imperial)	D \varnothing (Metric)	Seal Size Code	D1 (in)	D1 (mm)	D3 (in)	D3 (mm)	L1 (in)	L1 (mm)	L2 (in)	L2 (mm)	OEM Part Number
0.787	20.00	0200	1.378	35.00	1.34	34.00	0.866	22.00	0.283	7.20	11110086
0.984*	25.00	0250	1.496	38.00	1.50	38.00	0.965	24.50	0.374	9.50	11110087
1.181	30.00	0300	1.772	45.00	1.73	44.00	0.984	25.00	0.413	10.50	11110088
1.771*	45.00	0450	2.520	64.00	2.40	61.00	1.465	37.20	0.535	13.60	11110089

Please note, size code "0200" features a Vulcan Seals Type 19B boot stationary.

Dimensions in mm and inches

*Non-stock guarantee



^{®™} All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.

** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.

Embrace Excellence - Service | Quality | Value | Integrity

Mechanical Seals | FEP/PFA Encapsulated 'O'-rings | Gland Packing | Expanded PTFE Gasketing
UK/World: +44 (0) 114 249 3333 | USA: +1 952 955 8800 | www.vulcanseals.com | contact@vulcanseals.com