



Vulcan Seals Type 192G
Grundfos®
Technical Data Sheet



Product Description

The Vulcan Seals Type 192G is an elastomeric bellows seal with an ‘O’-ring mounted stationary designed to replace the Grundfos® seal styles “A” and “B” with a superior performing and easier-to-install seal design. The Vulcan Seals Type 192G is suitable for a wide range of older Grundfos® centrifugal pump ranges.

Why Choose the Vulcan Seals Type 192G Grundfos®?

Featuring the design benefits of the Vulcan Seals Type 192S but with fitting dimensions suitable for the seal chambers of this pump range.

Pump Ranges

The Grundfos® pump model includes the following pump ranges: "CR", "CRE" and "CRN" series.

Compliance & Certificates



Also available with built materials that adhere to the above compliance standards and certificates. Please enquire about your requirements.


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Seal Code
Viton™/FKM	VCP1 Carbon	VTN1 Tungsten Carbide	304 Stainless Steel	.V.E.
EP	VCP1 Carbon	VTN1 Tungsten Carbide	304 Stainless Steel	.E.E.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D3 (mm)	L1 (mm)	L2 (mm)
12.00	0120	23.00	24.00	25.90	15.00
16.00	0160	27.00	28.00	28.40	12.30
22.00	0220	37.00	36.50	30.00	11.10
33.00	0330	48.00	51.00	35.00	7.50

Dimensions in mm
*Non-stock guarantee



® ™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.
** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.