



Vulcan Seals Type 17B
Alfa Laval®
Technical Data Sheet



Product Description

The Vulcan Seals Type 17B Alfa Laval® is a Vulcan Seals Type 17 elastomer bellows encased rotary seal with a Vulcan Seals Type 20 boot-mounted stationary, to suit the seal chambers of Alfa Laval® LKR® agitators.

The Vulcan Seals Type 17B Alfa Laval® is available in additional sizes not appropriate to this data sheet, please see the Vulcan Seals Type 17 data sheet for details.

Why Choose the Vulcan Seals Type 17B Alfa Laval®?

The Vulcan Seals Type 17B Alfa Laval® is a direct replacement design to suit the original equipment, produced to Vulcan Seals’ manufacturing standards.

Pump Ranges

The Alfa Laval® pump model includes the following pump ranges: "LKR®" series agitators.

Compliance & Certificates



The Vulcan Seals mechanical seal range can be supplied with material combinations designed to meet the compliance standards and certifications listed above. Additional compliance or regulatory requirements can also be considered upon request. Please enquire to discuss your specific application.


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Material Code
EP [FDA COMPLIANT]	VCD1 Carbon	VSS1 Silicon Carbide	316 Stainless Steel	.E.DR.
EP	VCP1 Carbon	VSR1 Silicon Carbide	304 Stainless Steel	.E.D.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D2 (mm)	D3 (mm)	L1 (mm)	L2 (mm)
30.00	0300	50.80	45.80	53.00	26.90	11.99
35.00	0350	53.98	52.00	62.00	34.90	11.99

Dimensions in mm
*Non-stock guarantee



® ™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.

** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.