



Vulcan Seals Type 260B

Ebara®

Technical Data Sheet



Product Description

The Vulcan Seals Type 260B Ebara® range of elastomeric diaphragm double-ended seals, with boot stationaries at the oil side and bezel stationaries at the impeller side, to suit the seal chamber of various Ebara® and Tsurumi® submersible pumps. Suitable for submersible pumps, with the hard silicon carbide faces with bezel plate used at the impeller end of the installation, and the Carbon Ceramic faces at the bearing oil chamber end of the seal chamber. Vulcan Seals Type 260B Ebara® seals are supplied with replacement bezel-holding plates and car screws.

Why Choose the Vulcan Seals Type 260B Ebara®?

The Vulcan Seals Type 260B Ebara® seals are supplied complete with bezel plates for the inboard stationary.

Pump Ranges

The Ebara® pump model includes the following pump ranges: Certain Ebara® "DL", "DS" and "DW" range models.

Compliance & Certificates



The Vulcan Seals mechanical seal range can be supplied with material combinations designed to meet the compliance standards and certifications listed above. Additional compliance or regulatory requirements can also be considered upon request. Please enquire to discuss your specific application.


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Material Code
Viton™/FKM	VSR1 Silicon Carbide / VCP1 Carbon	VSR1 Silicon Carbide / VAW1 Ceramic	304 Stainless Steel	.V.WA.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D2 (mm)	D3 (mm)	D4 (mm)	L1 (mm)	L2 (mm)	L3 (mm)
20	0200	38.00	44.00	72.00	60.00	30.00	11.00	8.00
25	0250	44.00	50.00	72.00	60.00	32.00	11.00	8.00
30	0300	50.00	57.00	82.00	70.00	40.00	11.00	8.00
35	0350	58.00	65.00	94.00	80.00	41.00	11.00	9.00
40	0400	64.00	70.00	100.00	85.00	43.00	12.50	9.00
45	0450	66.00	70.00	105.00	90.00	44.00	12.00	9.00
50	0500	72.00	80.00	109.00	95.00	48.50	12.00	9.00

Dimensions in mm
*Non-stock guarantee



®™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.
** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.