



Vulcan Seals Type 1688Y

S.P.X. Johnson®

Technical Data Sheet



Product Description

The **Vulcan Seals Type 1688Y S.P.X. Johnson®** 'O'-ring mounted wave spring seals, with a very distinctive seat outer profile. 30mm size stationary has a single semicircular anti-rotation slot, other sizes have three flat anti-rotation slots.

Vulcan Seals also offers Vulcan Seals Type 1682Y S.P.X. Johnson® in 30mm and 35mm sizes, featuring a standard Vulcan Seals Type 1682 rotary with the **Vulcan Seals Type 1688Y S.P.X. Johnson®** stationary, which maybe the preferred option for these shaft sizes.

Suitable for Rotary lobe pumps, for highly viscous fluids and pastes in food and dairy industries.

Why Choose the Vulcan Seals Type 1688Y S.P.X. Johnson®?

The **Vulcan Seals Type 1688Y S.P.X. Johnson®** features the popular Vulcan Seals Type 1688 rotary with a unique and distinctive stationary profile to locate into the stationary recess of this range of rotary lobe pumps.

Each pump will require two seals, one for each drive shaft to the twin rotary lobes.

Pump Ranges

The S.P.X. Johnson® pump model includes the following pump ranges: "IC®" and "PD®" series lobe rotor pumps. Each pump requires two identical seals, one for each shaft.

Compliance & Certificates



The Vulcan Seals mechanical seal range can be supplied with material combinations designed to meet the compliance standards and certifications listed above. Additional compliance or regulatory requirements can also be considered upon request. Please enquire to discuss your specific application.


Standard Face Material Combinations

Elastomers	Rotary Face	Stationary Face	Metals	Complete Material Code
EP	304 Stainless Steel	VCP1 Carbon	304 Stainless Steel	.E.P.
EP	VTN2 Tungsten Carbide	VTN1 Tungsten Carbide	304 Stainless Steel	.E.H.
Viton™/FKM	304 Stainless Steel	VCP1 Carbon	304 Stainless Steel	.V.P.
Viton™/FKM	VTN2 Tungsten Carbide	VTN1 Tungsten Carbide	304 Stainless Steel	.V.H.

Dimensional Data

DØ (Metric)	Seal Size Code	D1 (mm)	D3 (mm)	L1 (mm)	L2 (mm)	OEM Ref.
30.00	0300	40.00	41.00	19.10	9.30	IC 10 , PD 10
35.00	0350	44.50	45.50	19.10	9.20	IC 20 , PD 20
50.00	0500	62.00	61.90	21.10	10.40	IC 30 , PD 30
70.00*	0700	85.00	88.90	25.80	14.10	IC 40 , PD 40
80.00*	0800	95.00	101.00	25.80	16.20	IC 50 , PD 50

Dimensions in mm
*Non-stock guarantee



® ™ All product names, brands and trademarks shown are property of their respective owners, are for identification purposes only, and do not imply affiliation nor endorsement.
** All dimensional and identification information shown is given in good faith and is based on extensive experience gained in business. Performance data is not provided for this product range based on the Vulcan Seals design being a replacement of, or an improvement on, a design that has originally proved suitable for the equipment and service concerned.