Fahnenmast-Versand

Tel.: 05222 / 9398312
info@fahnenmast-versand.de
www.fahnenmast-versand.de

Flag exposure:
dependent on
gusts of wind

Flag installation:
rope,
snap hooks
(attached to a flag)

Raising and
lowering the flag:
using an external rope
attached to a cleat
located 1,5m
above the ground



Reduction sleeve

ANODIZING:
15 micron

Wall thickness:
[5-6 m]
2/2,5 mm
[7-10m]
2/2,5/2,5 mm
[11-12 m]
2/2,5/2,5/3,5 mm



TOPS



Rotating socket
with a top



Silver onion
(aluminium)
(option)



Golden onion
(brass)
(option)

FLAG INSTALLATION



Rope



Cleat

BASES



Ground sleeve
(flagpoles 5-10 m)
To be installed
in a foundation



Hinged base
(flagpoles 5-12 m)
To be installed
in a foundation



Portable base

(for pavement
tiles 50x50 cm)

Height [m]	5	6	7	8	9	10	11	12
Sections no. [pcs.]	2	2	3	3	3	3	4	4
Tube diameter [mm]	50/65	50/65	50/65 80	50/65/ 80	50/65 80	50/65/ 80	50/65/ 80/95	50/65/ 80/95
Recommended maximum flag dimensions [m]	1,2 x 3 [3,6 m²]	1,2 x 3 [3,6 m²]	1,2 x 3,5 [4,2 m²]	1,2 x 3,5 [4,2 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]	1,5 x 4 [6 m²]