



# 9530 Series

Designed for ease of installation, the 9530 Series requires minimal steps and tools, reducing the time it takes to install the door. The 9530 Series is ideal for light-duty or self-storage applications.

◆ **Max opening size 10' x 10'**

Available in sizes up to 10' x 10' and in a variety of colors.

◆ **Warranty**

Three-year door warranty. For paint, 35-year no-fade, 40-year film integrity.

◆ **Options**

Insulated options available.

## Features



◆ **Easy to use tensioning device**

Each 9530 door uses a worm gear tensioning device that does not require special tools to apply or remove tension.



◆ **Installation / Operation**

Wear strips combined with a symmetrical headstop and round drum for quieter operation and an easier installation.



◆ **Industry standard seamed panel profile**

The panels are seamed together with the highest quality seaming process.

# 9530 Series

- 1 Brackets:** The brackets are 12-gauge reinforced galvanized steel.
- 2 Springs:** 12-gauge galvanized mounted by keyhole design for ease of installation
- 3 Door Curtain:** Industry standard profile, 26-gauge, Grade 80 prepainted steel
- 4 Bottom Bar:** 6063-T6 Aluminum extruded bottom bar with T-Bulb astragal.
- 5 Drums:** 9.5" stamped steel drum.
- 6 Head Stops:** 12-gauge galvanized mounted by keyhole design for ease of installation
- 7 Guides:** The 18-gauge galvanized steel guides are secured to the brackets and are fitted with polyethylene guide strips to provide smooth and quiet operation.

