



SMART  
THERMOSTAT  
**PRO**

No recharging or power stealing.  
It's the smart thermostat Pros trust.

#### 5-YEAR PRO INSTALL WARRANTY

Get our 3-year standard warranty plus  
2 years for pro purchase and install.



### Here's why pros love us.

#### RELIABLY POWERED

No common wire? No problem. Your ecobee comes with a Power Extender Kit so it doesn't rely on other equipment to charge itself.

#### COMPATIBLE WITH MOST

ecobee3 lite works with most HVAC systems including radiant heating systems, multistage, and dual fuel heat pumps. [ecobee.com/compatibility](http://ecobee.com/compatibility)

#### EASY INSTALLATION

Installation takes 30 minutes or less in most cases. We also offer easy access to HVAC tech support, wiring diagrams, and manuals if you ever need assistance.

#### SUPPORT HOURS

Available 8am-10pm (Mon-Fri) and 9am-9pm (Sat-Sun). **1.866.518.6740** | [support@ecobee.com](mailto:support@ecobee.com)

### Here's why consumers love us.

#### CONTROL FROM ANYWHERE, ANYTIME

Customers can easily control temperature and settings from anywhere with an Apple Watch, Android, or iOS device.

#### AVERAGE 23% SAVINGS\*

When customers bring home the ecobee3 lite, they save an average of 23% annually on heating and cooling costs. \*Learn more at [ecobee.com/savings](http://ecobee.com/savings)

#### UPDATES YOU AS NEEDED

ecobee3 lite monitors heating and cooling systems, and alerts customers if it senses something is wrong.



SMART  
THERMOSTAT  
**PRO**



No recharging or power stealing.  
It's the smart thermostat Pros trust.

## TECH SPECS

### COMPATIBILITY

Conventional (2H/2C)—Gas, Oil, Electric.  
Boiler (2-stage-heating).  
Air-Cooled & Geo-Thermal Heat pumps  
(2 stage heat pump + 2 stage aux heat/2  
cool) (4H/2C).  
Duel-Fuel support.

### WIRE TERMINALS

RC	O/B	W1
G	RH	W2
Y1	C	PEK
Y2		

### POWERING METHOD

Wired 24VAC through terminals C or Rc.  
Power Extender Kit enables you to reliably  
power your thermostat without having  
to run a C wire.

### POWER CONSUMPTION

Less than 3.5VA

### CONNECTIVITY AND SECURITY

Wi-Fi, IEEE 802.11 b/g/n @ 2.4 GHz  
Wi-Fi Protected Access (WPA/WPA2)  
Wired Equivalent Privacy (WEP)  
DHCP (dynamic) or static IP addressing  
Transport Layer Security (TLS)

### BANDWIDTH

15-20 MB/month

### SUSTAINABILITY

Mercury free  
Arsenic free  
PVC free  
ROHS compliant

### THERMOSTAT SENSORS

Temperature  
Proximity  
Humidity

### TEMPERATURE RANGE

Temperature: 45° to 92°F (7° to 33°C)  
Display: 40° to 100°F (5° to 37°C)  
Sensitivity: +/- 1°F (+/- 0.5°C)  
Operating: 32° to 130°F (0° to 55°C)

### HUMIDITY RANGE

Display: 20% to 90% RH  
Sensitivity: +/- 5% RH  
Operating: 5% to 95% RH (non condensing)

### STORAGE

-31° to 113°F (-35° to 45°C)  
5% to 95% RH (non condensing)

### WARRANTY

5-year warranty  
(PRO Install only)

### LANGUAGES

English

### DISPLAY

3.5" full-color LCD touch screen  
320 x 480 pixel display

### HOMEKIT-ENABLED

HomeKit requires an iPhone, iPad, or iPod  
touch with iOS 9 or later. Controlling  
HomeKit-enabled accessories away from  
home requires an Apple TV with tvOS 9.0 or  
later and an iPhone, iPad, or iPod touch with  
iOS 9 or later.

### WHAT'S IN THE BOX

ecobee3 lite thermostat  
Install guide  
Backplate  
Trim plate  
Screws  
Dry wall plugs  
Wire labels  
Power Extender Kit

### PRODUCT DIMENSIONS

Thermostat  
Length: 102.88 mm  
Width: 102.88 mm  
Depth: 21.4 mm

Trim Plate  
Length: 170 mm  
Width: 170 mm  
Depth: 6.25 mm


Power Extender Kit  
Length: 62.1 mm  
Width: 60.1 mm  
Depth: 21.4 mm

### WORKS WITH



## Enhance the way your customers experience comfort.

With SmartSensor placed in multiple rooms, your customers can set an average temperature for their home and experience better comfort throughout.



### SMARTER COMFORT

Helps manage hot or cold spots by setting an average temperature, keeping your customer's whole home comfortable.

### HEIGHTENED SENSES

Detects occupancy, allowing for room-specific comfort where your customers want it, when they want it.

### FURTHER SAVINGS

Signals the thermostat to start saving when your customer is not home, keeping their energy bill in check.

## TECH SPECS

### COMPATIBILITY

ecobee SmartThermostat with voice control  
ecobee SmartThermostat Pro with voice control  
ecobee4  
ecobee4 Pro  
ecobee3 lite  
ecobee3 lite Pro  
ecobee3

### POWERING METHOD

CR2477 battery

### BATTERY LIFE

Up to 5 years

### CONNECTIVITY

915MHz

### SENSORS

Temperature  
Occupancy

### WARRANTY

3 years

### RANGE

50 ft\*

### MOUNTING

Detachable stand  
Wall mounting bracket

### STORAGE

Temperature: -31°F to 113°F  
(-35°C to 45°C)  
Humidity: 5% to 95% RH

### WHAT'S IN THE BOX

2 SmartSensor  
2 Detachable Stands  
2 Batteries  
Install Guide  
Adhesive  
2 Wall Mounting Brackets

### PRODUCT DIMENSIONS

Length: 40 mm (1.58 in)  
With stand: 50 mm (1.58 in)  
Width: 40 mm (1.6 in)  
Depth: 26.4 mm (1.03 in)

\* Up to 50 feet away from your ecobee smart thermostat. Range varies according to outstanding factors including wireless connectivity and individual home structure and arrangement.