

P28 - LOUDSPEAKER

Main Channels

INTRODUCTION

The P28 is capable of massive output despite its size, it is an 8 meter THX reference level speaker with an 80 Hz crossover. It has the same dynamic capability as the P815. We've taken the acclaimed P8 speaker design and increased its maximum output level 6 dB with a second custom 8" mid-woofer. Delivering the same impeccable audio quality with incredible headroom. Its D'Appolito design minimizes floor and ceiling reflections for improved audio quality. When you need maximum dynamic range, especially in very large rooms, but can't accommodate the size of a full-range Procella speaker, the P28 is the powerful choice!

TECHNICAL SPECIFICATIONS

Impedance	4 ohms nominal Above 6 ohms working range Phase angles less than 30 degrees	Components	
		Midrange	2x 8" driver with 40mm voice coil in 35 litre sealed box
Power Handling		High Frequency	1.5' driver with a polyester diaphragm on elliptical constant directivity waveguide
Continuous	500W		
Peak	>1.000W		
Frequency Response		Connectivity	
-3dB	75Hz and 20Hz		Gold plated large diameter binding posts
Maximum SPL		Included	Flushmount wall bracket
Freestanding	122dB continuous 128dB peak	Dimensions	
In wall	128dB continuous 132dB peak	HxWxD	24.4" x 17.7" x 7.5 620 x 450 x 190mm
Dispersion Pattern		Shipping Carton	
-6dB	Constant directivity; 80°H x 35°V from 1.5kHz	HxWxD	29.5" x 22.4" x 11.8" 750 x 570 x 300mm
Sensitivity		Net Weigth	46.3 Lbs / 21 Kg
1m/1W	95dB	Shipping Weight	50.7Lbs / 23 Kg
Crossover	Asymmetrical Linkwitz-Riley 1.6kHz, BSC	Assembly	Sweden; 100% QC testing
Finish	Black painted finish		
Construction	Void free MDF internally cross braced		

