

P15

SOUND

PROCELLA®

PERFECTED

Dual 15 Inch Passive Subwoofer

INTRODUCTION

In an astonishingly compact enclosure (just 8.75" / 222mm deep), the P15 subwoofer brings the authority and impact of the mighty P18 to medium and small rooms where nothing less than the best bass quality will do. Its dual 15-inch long-throw Italian pro audio subwoofer drivers have 3" voice coils and are mounted in a sealed-box heavily-braced enclosure. The P15 is driven by external amplification with DSP. The P15 blends lightning-quick transient response with massive impact. Capable of 125dB output and able to reproduced bass frequencies in-room flat to 22Hz and below, the P15 is the ideal low-frequency source for mid-sized domestic and professional environments.

TECHNICAL SPECIFICATIONS

Impedance Each driver is 8 ohms nominal

Frequency Response
-3dB 22Hz

Maximum SPL @ 50Hz
Continuous 119dB
Peak 125dB

Components Dual long-throw pro audio drivers with cast aluminium. Chassis and ferrite magnets in 75l sealed box.

Power Handling
Continuous 2 x 800W
Peak 2 x 1.600W

Sensitivity
1m/1W 97dB

Connectivity Dual gold plated binding posts.
One input per driver

Construction Heavily internally braced MDF,
Black painted finish

Dimensions
HxWxD 22.4" x 36.6" x 8.75"
570 x 930 x 222 mm

Shipping Carton
HxWxD 27.2" x 42.5" x 15"
690 x 1080 x 380 mm

Net Weigth 92 Lbs / 41,7 Kg

Shipping Weight 105 Lbs / 47,7 Kg (plus pallet)

Included Damper feet, parallel input cables

Assembly Sweden; 100% QC testing

Amplification External amplifier is required

Two channels of external amplification are required.
Procella amplifiers are sold and packaged seperately.
See Tech Sheets for specifications.

