

P10Si Mk2 - SUBWOOFER



Single 10 Inch Passive Subwoofer

INTRODUCTION

The upgraded P10Si Mk2 elevates performance to a higher level compared to the original P10Si, with greater output and low frequency extension. This new version has the same dual applications as a balancing subwoofer and as the low frequency component of the P610Mk2 full-range loudspeaker. With a new, higher-performance 10 inch driver in a larger enclosure, the updated Mk2 version's increased output capability improves its performance not only as a balancing subwoofer but as a more capable stand-alone subwoofer. It also completes the full-bandwidth of the P610 Mk2 when used as the three-way speaker's biamplified woofer element in combination with the P6 Mk2 upgrade.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal	Dimensions	18,1" x 18,9" x 8,6" HxWxD
Frequency Response -3dB	26Hz	Shipping Carton HxWxD	460 x 480 x 220 mm (rubber feet +12mm)
Maximum SPL @ 50Hz Continuous Peak	109dB 115dB	Net Weight	55,1 Lbs / 25 Kg
Components	10 inch long-throw driver with 65mm voice coil, 35 litre sealed box	Shipping Weight	59,52 Lbs / 27 Kg
Power Handling Continuous Peak	400W 1.000W	Included	Damper feet
Sensitivity 1m/1W	94dB	Assembly	Belgium; 100% QC testing
Connectivity	Gold plated binding posts	Amplification	External amplifier is required
Construction	Void free MDF internally cross braced	Recommended	One channel of DA03-DSP or one channel of DA08-DSP
		Procella Amplifiers are sold and packaged seperately <i>DA03-DSP and DA08-DSP amplifiers include DSP presets for the P610 Mk2 and P10Si Mk2</i>	

