

P5V - LOUDSPEAKER



Main, Surround & Height Channels

INTRODUCTION

The P5V delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver.

The P5V comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal Phase angles less than 45 degrees
Power Handling Continuous Peak	75W 250W
Frequency Response -3dB	90Hz and 20Hz
Maximum SPL Freestanding Peak In wall Peak	107dB continuous 113dB 113dB continuous 119dB
Dispersion Pattern -6dB	Constant directivity; 80° circular from 2.5kHz
Sensitivity 1m/1W	91dB
Crossover	Asymmetrical, phase aligned 2.2kHz, BSC
Finish	White or Black semi-matte painted
Recommended Amplifier	1-ch DA03-DSP

Components Midrange	5.25" driver with 26mm voice coil in 5 litre sealed box
High Frequency	1" compression driver on a circular constant directivity waveguide
Connectivity	Gold plated large diameter binding posts
Wall Mount	1 Inserts for VESA 100 bracket and keyholes provided for both vertical and horizontal mounting
Dimensions HxWxD	18.5" x 7.5" x 4.5" 470 x 190 x 115 mm
Shipping Carton HxWxD	23.6" x 11.6" x 7.9" 600 x 295 x 200 mm
Net Weigth	11 Lbs / 5 Kg
Shipping Weight	13.2Lbs / 6 Kg
Assembly	Belgium; 100% QC testing

