

P15Si - SUBWOOFER

Single 15 Inch Passive Subwoofer

INTRODUCTION

The P15Si is intended as the LF part of the P815 and can also be used as a balancing subwoofer. As the Lf part of the P815, the P15 Si can produce THX cinema reference levels at an incredible 8 meters (over 26 feet). The subwoofer requires external amplification. It provides both DSP crossover and amplification for the P8 mid/high-frequency module and the P15Si low-frequency module. The P15Si is producing the awesome impact of a full-scale 96/24 recording or film soundtrack. The P15Si is for integration into professional rooms, including THX Certified Screening Rooms and THX pm3 (professional Mixing, Monitoring and Mastering) studios.

TECHNICAL SPECIFICATIONS

Impedance 8 ohms nominal

Frequency Response
-3dB 22Hz

Maximum SPL @ 50Hz
Continuous 113dB
Peak 119dB

Components 15 inch long-throw driver with
75mm voice coil in 51 litre sealed
box

Power Handling
Continuous 600W
Peak 1500W

Sensitivity
1m/1W 93dB

Connectivity Gold plated binding posts

Construction Void free MDF, internally cross-
braced, Painted black finish

Dimensions 22,5" x 18,825" x 11"
HxWxD 570 x 480 x 280 mm

Shipping Carton 28,35" x 23,6" x 15,75"
HxWxD 720 x 600 x 400 mm

Net Weigth 52,9 Lbs / 24 Kg

Shipping Weight 63,9 Lbs / 29 Kg

Included Damper feet

Assembly Belgium; 100% QC testing

Amplification External amplifier is required

Recommended 1-ch DA03-DSP or 1-ch DA08-DSP

Procella Amplifiers are sold and packaged seperately

SOUND
PERFECTED

PROCELLA®

