

P28 Mk3 - LOUDSPEAKER

SOUND

PROCELLA

PERFECTED

Main Channels

INTRODUCTION

The P28Mk3 is capable of massive output despite its size, it is an 8 meter THX reference level speaker with an 80 Hz cross-over. It has the same dynamic capability as the P815. We've taken the acclaimed P8 speaker design and increased its maximum output level 6 dB with a second custom 8" mid-woofer. Delivering the same impeccable audio quality with incredible headroom. Its D'Appolito design minimizes floor and ceiling reflections for improved audio quality. When you need maximum dynamic range, especially in very large rooms, but can't accommodate the size of a full-range Procella speaker, the P28 is the powerful choice!

TECHNICAL SPECIFICATIONS

Impedance	8ohms nominal
Power Handling	
Rated	400W
Peak	800W
Frequency Response	
-3dB	75Hz and 20Hz
Maximum SPL	
Freestanding	122dB continuous 128dB peak
In wall	128dB continuous 132dB peak
Dispersion Pattern	
-6dB	Constant directivity; 80°H x 35°V from 1.5kHz
Sensitivity	
1m/1W	94.3dB
Crossover	Asymmetrical Linkwitz-Riley 1.6kHz, BSC
Finish	Black painted finish
Construction	Void free MDF internally cross braced

Components	
Midrange	2x 8" driver with 2" voice coil
High Frequency	1.7" driver
Connectivity	Gold plated large diameter binding posts
Included	Flushmount wall bracket
Dimensions	
HxWxD	24.4" x 17.7" x 7.5 620 x 450 x 190mm
Shipping Carton	
HxWxD	29.5" x 22.4" x 11.8" 750 x 570 x 300mm
Net Weigth	46.3 Lbs / 21 Kg
Shipping Weight	50.7Lbs / 23 Kg
Recommended Amplifier	1-ch DA03-DSP
Assembly	Belgium; 100% QC testing

