P21si - SUBW00FER

SOUND

PERFECTED

Single 21 Inch Passive Subwoofer

INTRODUCTION

Today's highest-performance systems demand serious low-frequency authority, and the P21Si delivers. Building on Procella's sealed-box heritage, this single 21" subwoofer combines immense output with tight, accurate control, making it the perfect solution where ultra-deep extension meets space efficiency. Using the same driver technology found in our flagship V21, the P21Si's 110-litre enclosure houses a 21" professional-grade driver with a 4.5" voice coil and neodymium magnet, achieving -3dB at 21Hz with remarkable transient precision. Capable of 124.7 dB continuous and 127.4 dB peak SPL @ 50Hz, the P2ISi delivers cinematic bass in a compact form. Paired with the Procella DA08-DSP amplifier, it becomes a full-frequency powerhouse.

TECHNICAL SPECIFICATIONS

8 ohms nominal **Impedance**

Frequency Response

21Hz -3dB

Maximum SPL @ 50Hz

Continuous 124.7dB Peak 127.4dB

Professional 21" driver Components

4.5" voice coil

Neodymium magnet 110 litre sealed enclosure

Power Handling

1800W Continuous 3600 W Peak

Sensitivity

1m/1W 97dB

Connectivity Gold plated binding posts

Construction Internal heavily braced MDF

Semi-matte textured black lacquer

Dimensions 805x700x290mm (grille 300mm) HxWxD

31.7x27.6x11.4 inch (grille 11.8)

Shipping Carton

803x908x375mm HxWxD

Net Weigth 48 Kg

Shipping Weight 52 Ka

Assembly Belgium; 100% QC testing

Amplification 2-ch bridge* DA08-DSP

* depending on the roomsize / listening position in combination with the desired SPL

Procella Amplifiers are sold and packaged seperately



