

U24 - SUBWOOFER



Single 24 Inch Passive Subwoofer

INTRODUCTION

The U24 redefines single-driver performance. With a professional 24" driver, 6" voice coil, and neodymium magnet in a 148-litre sealed enclosure, it delivers effortless extension down to 19Hz (-3dB) with absolute precision. Capable of 126.8 dB continuous and 129.8 dB peak SPL @ 50Hz, the U24 brings commanding, ultra-deep bass to large-scale systems that demand uncompromising control and impact. Paired with the Procella DA08-DSP in bridged mode, it unlocks reference-level low-frequency power with stunning clarity.

Perfect for flagship cinemas and high-end installations where “enough” is never enough.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal	Dimensions	HxWxD	805x700x380mm (grille 390mm)
Frequency Response -3dB	19Hz	Shipping Carton	HxWxD	803x908x454mm
Maximum SPL @ 50Hz Continuous Peak	126.8dB 129.8dB	Net Weight		69 Kg
Components	Professional 24" driver 6" voice coil Neodymium magnet 148 litre sealed enclosure	Shipping Weight		74 Kg
Power Handling Continuous Peak	2400W 4800W	Assembly		Belgium; 100% QC testing
Sensitivity 1m/1W	98dB	Amplification		2-ch bridge DA08-DSP
Connectivity	Gold plated binding posts	Procella Amplifiers are sold and packaged separately		
Construction	Internal heavily braced MDF Semi-matte textured black lacquer			

