

P15A - SUBWOOFER



Single 15 Inch Active Subwoofer

INTRODUCTION

Expanding the Procella subwoofer lineup in a slim, compact profile, the P15A is available in both black and white finishes. The 15 inch professional woofer driver features a 3 inch voice coil and cast aluminum chassis. The built in Procella-designed amplifier delivers 350 Watts of class-D power, enabling the subwoofer to deliver 119 dB of output at 50 Hz. For room-shaking low frequencies, the P15A extends down to a -3dB point of 24 Hz. Both XLR and RCA inputs are provided, and switchable room settings optimize the subwoofer's response for room boundary conditions. Thanks to its compact size and slim profile, the P15A is a highly versatile solution. Its performance is outstanding whether in small to medium size rooms or in larger theaters where multiple subwoofers must be accommodated.

TECHNICAL SPECIFICATIONS

Frequency Response -3dB	24Hz	Power Consumption	Standby <0.5W Full Power 440W
Maximum SPL @ 50Hz Continuous Peak	113dB 119dB	Safety Approval	CE, FCC, CCC
Components	Long-throw 15" driver with 3 inch voice coil and cast aluminum chassis in 55 litre sealed box	Construction	Heavily braced MDF White or Black matte finish matching steel grille
Polarity	Switchable Normal/Reversed	Dimensions WxHxD	19,89" x 27,54" x 9,65" 505 x 700 x 245 mm
Room Settings	Against wall, In corner	Shipping Carton WxHxD	23,6" x 28,35" x 15,75" 600 x 720 x 400 mm
Amplifier	Built in 350W, Digital Class D	Net Weight	52,9 Lbs / 24 Kg
Connectivity	Single balanced XLR Single RCA input Single RCA output	Shipping Weight	63,9 Lbs / 29 Kg
Line input	50-80Hz switchable 110-240Hz	Included	Rubber mounting feet Power Cord
Finish	Black or white semi-matte painted finish with matching steel grille	Assembly	Belgium; 100% QC testing
Standby	Programmable		

