

# P18 - SUBWOOFER



## Dual 18 Inch Passive Subwoofer

### INTRODUCTION

The P18 is producing awesome low-frequency energy, its pure visceral bass fills even the largest rooms with seemingly unlimited headroom. In a class by itself, the P18 is the only subwoofer for those seeking the aural immersion of the reference cinema and live concert experience. This gives the subwoofer a stunning 134 dB (139 dB peak) output capability, and sub-bass extension to down below 18 Hz. The P18 is THX Approved for integration into professional rooms, including THX Certified Screening Rooms and THX pm3 Studios (professional mixing, monitoring, and mastering).

### TECHNICAL SPECIFICATIONS

**Impedance** Each driver is 8 ohms nominal

**Frequency Response**  
-3dB 21Hz

**Maximum SPL @ 50Hz**  
Continuous 133dB  
Peak 139dB

**Components** Dual long-throw professional 18" drivers with 4" voice coil. Aluminum demodulation ring and Neodymium magnets in 205 litre sealed box

**Power Handling**  
Continuous 2 x 1,200W  
Peak 2 x 3,000W

**Sensitivity**  
1W/1m 102dB

**Connectivity** Dual gold plated binding posts.  
One input per driver

**Construction** Heavily internally braced MDF Semi matte textured black paint finish

**Dimensions** 26.4" x 41.3" x 11.8"  
WxHxD 670 x 1050 x 300 mm

**Shipping Carton** 31.5"x47.25"x15.75"  
WxHxD 800 x 1200 x 400 mm

**Net Weight** 132 Lbs / 60 Kg

**Shipping Weight** 143 Lbs / 65 Kg (plus pallet)

**Included** Damper feet, parallel input cables

**Assembly** Belgium; 100% QC testing

**Recommended Amplifier** 2-ch DA08-DSP

**Procella amplifiers are sold and packaged seperately.**

