

U12 - SUBWOOFER



Single 12 Inch Passive Subwoofer

INTRODUCTION

Part of the new UNO Series, the U12 introduces a refined approach to low-frequency performance. Built for precision, control, and seamless integration across a wide range of systems. Equipped with a 12" long-throw driver in a sealed enclosure, it delivers fast, accurate bass down to 25Hz. No excess, no boom, just clean, controlled low-end that stays true to the content. Compact in size but capable in output, the U12 is designed to scale effortlessly, whether in smaller rooms or as part of a larger multi-sub setup.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal
Frequency Response -3dB	25Hz
Maximum SPL @ 50Hz Continuous Peak	108dB 114dB
Components	12 inch long-throw driver with 75mm voice coil in a 30 litre sealed box
Power Handling Continuous Peak	450W 900W
Sensitivity 1W/1m	90.5dB
Connectivity	Gold plated binding posts
Construction	Void free MDF, internally cross- braced, painted black finish

Dimensions WxHxD	450x504x191mm (+10 grille)
Shipping Carton WxHxD	528x588x278mm
Net Weight	19Kg
Shipping Weight	21Kg
Included	Damper Feet
Assembly	Belgium; 100% QC tested
Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended
Procella Amplifiers are sold and packaged separately	

