

# U15 - SUBWOOFER



## Single 15 Inch Passive Subwoofer

### INTRODUCTION

Part of the new UNO Series, the U15 builds on the foundation of the U12 with increased output, deeper extension, and greater headroom. Featuring a 15" long-throw driver in a sealed enclosure, it reaches down to 22Hz with authority and control. Tight, articulate bass that delivers impact without sacrificing precision. Designed for medium to large rooms, the U15 offers the perfect balance between power and accuracy, making it a versatile choice for high-performance cinema systems and demanding listening environments.

### TECHNICAL SPECIFICATIONS

<b>Impedance</b>	8 Ohms nominal
<b>Frequency Response</b> -3dB	22Hz
<b>Maximum SPL @ 50Hz</b> Continuous Peak	113dB 119dB
<b>Components</b>	15 inch long-throw driver with 75mm voice coil in a 48 litre sealed box
<b>Power Handling</b> Continuous Peak	450W 900W
<b>Sensitivity</b> 1W/1m	93.8dB
<b>Connectivity</b>	Gold plated binding posts
<b>Construction</b>	Void free MDF, internally cross- braced, painted black finish

<b>Dimensions</b> WxHxD	540x621x202mm (+10 grille)
<b>Shipping Carton</b> WxHxD	628x708x300mm
<b>Net Weight</b>	25Kg
<b>Shipping Weight</b>	27Kg
<b>Included</b>	Damper Feet
<b>Assembly</b>	Belgium; 100% QC tested
<b>Amplification</b>	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended
<b>Procella Amplifiers are sold and packaged separately</b>	

