

P15A - SUBWOOFER

Single 15 Inch Active Subwoofer

INTRODUCTION

Expanding the Procella subwoofer lineup in a slim, compact profile, the P15A is available in both black and white finishes. The 15 inch professional woofer driver features a 3 inch voice coil and cast aluminum chassis. The built in Procella-designed amplifier delivers 350 Watts of class-D power, enabling the subwoofer to deliver 119 dB of output at 50 Hz. For room-shaking low frequencies, the P15A extends down to a -3dB point of 24 Hz. Both XLR and RCA inputs are provided, and switchable room settings optimize the subwoofer's response for room boundary conditions. Thanks to its compact size and slim profile, the P15A is a highly versatile solution. Its performance is outstanding whether in small to medium size rooms or in larger theaters where multiple subwoofers must be accommodated.

TECHNICAL SPECIFICATIONS

Frequency Response

-3dB 24Hz

Maximum SPL @ 50Hz

Continuous 113dB
Peak 119dB

Components

Long-throw 15" driver with 3 inch voice coil and cast aluminum chassis in 55 litre sealed box

Polarity

Switchable Normal/Reversed

Room Settings

Against wall, In corner

Amplifier

Built in 350W, Digital Class D

Connectivity

Single balanced XLR
Single RCA input
Single RCA output

Line input

50-80Hz
switchable 110-240Hz

Finish

Black or white semi-matte painted finish with matching steel grille

Standby

Programmable

Power Consumption

Standby <0.5W
Full Power 440W

Safety Approval

CE, FCC, CCC

Construction

Heavily braced MDF
White or Black matte finish
matching steel grille

Dimensions

WxHxD 19,89" x 27,54" x 9,65"

505 x 700 x 245 mm

Shipping Carton

WxHxD 23,6" x 28,35" x 15,75"

600 x 720 x 400 mm

Net Weight

52,9 Lbs / 24 Kg

Shipping Weight

63,9 Lbs / 29 Kg

Included

Rubber mounting feet
Power Cord

Assembly

Belgium; 100% QC testing

