

P18 - SUBWOOFER

Dual 18 Inch Passive Subwoofer



INTRODUCTION

The P18 is producing awesome low-frequency energy, its pure visceral bass fills even the largest rooms with seemingly unlimited headroom. In a class by itself, the P18 is the only subwoofer for those seeking the aural immersion of the reference cinema and live concert experience. This gives the subwoofer a stunning 134 dB (139 dB peak) output capability, and sub-bass extension to down below 18 Hz. The P18 is THX Approved for integration into professional rooms, including THX Certified Screening Rooms and THX pm3 Studios (professional mixing, monitoring, and mastering).

TECHNICAL SPECIFICATIONS

Impedance Each driver is 8 ohms nominal

Frequency Response
-3dB 21Hz

Maximum SPL @ 50Hz
Continuous 133dB
Peak 139dB

Components Dual long-throw professional 18" drivers with 4" voice coil. Aluminum demodulation ring and Neodymium magnets in 205 litre sealed box

Power Handling
Continuous 2 x 1,200W
Peak 2 x 3,000W

Sensitivity
1W/1m 102dB

Connectivity Dual gold plated binding posts.
One input per driver

Construction Heavily internally braced MDF Semi matte textured black paint finish

Dimensions 26.4" x 41.3" x 11.8"
WxHxD 670 x 1050 x 300 mm

Shipping Carton 31.5"x47.25"x15.75"
WxHxD 800 x 1200 x 400 mm

Net Weight 132 Lbs / 60 Kg

Shipping Weight 143 Lbs / 65 Kg (plus pallet)

Included Damper feet, parallel input cables

Assembly Belgium; 100% QC testing

Recommended Amplifier 2-ch DA08-DSP

Procella amplifiers are sold and packaged separately.

