

U12 - SUBWOOFER



Single 12 Inch Passive Subwoofer

INTRODUCTION

Part of the new UNO Series, the U12 introduces a refined approach to low-frequency performance. Built for precision, control, and seamless integration across a wide range of systems. Equipped with a 12" long-throw driver in a sealed enclosure, it delivers fast, accurate bass down to 25Hz. No excess, no boom, just clean, controlled low-end that stays true to the content. Compact in size but capable in output, the U12 is designed to scale effortlessly, whether in smaller rooms or as part of a larger multi-sub setup.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal	Dimensions	
		WxHxD	450x504x191mm (+10 grille)
Frequency Response		Shipping Carton	
-3dB	25Hz	WxHxD	528x588x278mm
Maximum SPL @ 50Hz		Net Weight	19 Kg
Continuous	108dB	Shipping Weight	22 Kg
Peak	114dB	Included	Damper Feet
Components	12 inch long-throw driver with 75mm voice coil in a 30 litre sealed box	Assembly	Belgium; 100% QC tested
Power Handling		Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended
Continuous	450W	Procella Amplifiers are sold and packaged separately	
Peak	900W		
Sensitivity			
1W/1m	90.5dB		
Connectivity	Gold plated binding posts		
Construction	Void free MDF, internally cross- braced, painted black finish		

