

U18 - SUBWOOFER



Single 18 Inch Passive Subwoofer

INTRODUCTION

Part of the new UNO Series, the U18 is built for maximum output, extension, and control in demanding environments. Driven by an 18" long-throw driver in a sealed enclosure, it reaches down to 21Hz with authority, delivering deep, physical bass while maintaining precision and speed. High SPL capability ensures consistent performance, even in large rooms or high-impact cinema systems. Designed for scale, the U18 anchors larger setups with effortless low-end, whether used as a single unit or in multi-sub configurations. Power, control, and clarity, without compromise.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal	Dimensions	
		WxHxD	592x681x246(+10 grille)mm
Frequency Response -3dB	21Hz	Shipping Carton WxHxD	765x340x642mm
Maximum SPL @ 50Hz Continuous Peak	127dB 133dB	Net Weight	33 Kg
Components	18 inch long-throw driver with 100mm voice coil in a 75 litre sealed box	Shipping Weight	36 Kg
Power Handling Continuous Peak	1200W 2400W	Included	Damper Feet
Sensitivity 1W/1m	96dB	Assembly	Belgium; 100% QC tested
Connectivity	Gold plated binding posts	Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended
Construction	Void free MDF, internally cross- braced, painted black finish	Procella Amplifiers are sold and packaged separately	

