

U15 - SUBWOOFER

Single 15 Inch Passive Subwoofer



INTRODUCTION

Part of the new UNO Series, the U15 builds on the foundation of the U12 with increased output, deeper extension, and greater headroom. Featuring a 15" long-throw driver in a sealed enclosure, it reaches down to 22Hz with authority and control. Tight, articulate bass that delivers impact without sacrificing precision. Designed for medium to large rooms, the U15 offers the perfect balance between power and accuracy, making it a versatile choice for high-performance cinema systems and demanding listening environments.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal	Dimensions	
		WxHxD	540x621x202mm (+10 grille)
Frequency Response		Shipping Carton	
-3dB	22Hz	WxHxD	628x708x300mm
Maximum SPL @ 50Hz		Net Weight	25 Kg
Continuous	113dB	Shipping Weight	28 Kg
Peak	119dB	Included	Damper Feet
Components	15 inch long-throw driver with 75mm voice coil in a 48 litre sealed box	Assembly	Belgium; 100% QC tested
Power Handling		Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended
Continuous	450W	Procella Amplifiers are sold and packaged separately	
Peak	900W		
Sensitivity			
1W/1m	93.8dB		
Connectivity	Gold plated binding posts		
Construction	Void free MDF, internally cross- braced, painted black finish		

