P15A - SUBWOOFER

SOUND PROCELLA PERFECTED

Single 15 Inch Active Subwoofer



INTRODUCTION

Expanding the Procella subwoofer lineup in a slim, compact profile, the P15A is available in both black and white finishes. The 15 inch professional woofer driver features a 3 inch voice coil and cast aluminum chassis. The built in Procella-designed amplifier delivers 350 Watts of class-D power, enabling the subwoofer to deliver 119 dB of output at 50 Hz. For room-shaking low frequencies, the P15A extends down to a -3dB point of 24 Hz. Both XLR and RCA inputs are provided, and switchable room settings optimize the subwoofer's response for room boundary conditions. Thanks to its compact size and slim profile, the P15A is a highly versatile solution. Its performance is outstanding whether in small to medium size rooms or in larger theaters where multiple subwoofers must be accommodated.

TECHNICAL SPECIFICATIONS

Frequency Response	
-3dB	24Hz
Maximum SPL @ 50Hz	
Continuous	113dB
Peak	119dB
Components	Long-throw 15" driver with 3 inch voice coil and cast aluminum chassis in 55 liter sealed box
Polarity	Switchable Normal/Reversed
Room Settings	Against wall, In corner
Amplifier	Built in 350W, Digital Class D
Connectivity	Single balanced XLR Single RCA input Single RCA output
Line input	50-80Hz switchable 110-240V
Finish	Black or white semi-matte painted finish with matching steel grille
Standby	Programmable
Power Consumption	Standby <0.5W Full Power 440W
Safety Approval	CE, FCC, CCC
Construction	Heavily braced MDF White or Black matte finish matching steel grille
Dimensions	19.89" x 27.54" x 9.65"
WxHxD	505 x 700 x 245 mm
Shipping Carton	23.6" x 28.35" x 15.75"
WxHxD	600 x 720 x 400 mm
Net Weight	52.9 Lbs / 24 Kg
Shipping Weight	63.9 Lbs / 29 Kg
Included	Rubber mounting feet Power Cord
Assembly	Belgium; 100% QC testing



Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio