P15Si - SUBWOOFER

SOUND PROCELLA PERFECTED

Single 15 Inch Passive Subwoofer





INTRODUCTION

The P15Si is intended as the LF part of the P815 and can also be used as a balancing subwoofer. As the LF part of the P815, the P15Si can produce THX cinema reference levels at an incredible 8 meters (over 26 feet). The subwoofer requires external amplification, which provides both DSP crossover and amplification for the P8 mid/high-frequency module and the P15Si low-frequency module. The P15Si is producing the awesome impact of a full-scale 96/24 recording or film soundtrack. The P15Si is for integration into professional rooms, including THX Certified Screening Rooms and THX pm3 (professional Mixing, Monitoring and Mastering) studios.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal
Frequency Response	
-3dB	22Hz
Maximum SPL @ 50Hz	
Continuous	113dB
Peak	119dB
Components	15 inch long-throw driver with 75mm voice coil in 51 liter sealed box
Power Handling	
Continuous	600W
Peak	1,500W
Sensitivity	
1m/1W	93dB
Connectivity	Gold plated binding posts
Construction	Void free MDF, internally cross-braced, Painted black finish

Dimensions	22.5” x 18.825” x 11”
HxWxD	570 x 480 x 280 mm
Shipping Carton	28.35” x 23.6” x 15.75”
HxWxD	720 x 600 x 400 mm
Net Weight	52.9 Lbs / 24 Kg
Shipping Weight	63.9 Lbs / 29 Kg
Included	Damper feet
Assembly	Belgium; 100% QC testing
Amplification	External amplifier is required
Recommended	1-ch DA03-DSP or 1-ch DA08-DSP

Procella Amplifiers are sold and packaged separately

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio