P10Si MK2 - SUBWOOFER

SOUND PERFECTED

PROCELLA

Single 10 Inch Passive Subwoofer





INTRODUCTION

The upgraded P10Si Mk2 elevates performance to a higher level compared to the original P10Si, with greater output and low frequency extension. This new version has the same dual applications as a balancing subwoofer and as the low frequency component of the P610Mk2 full-range loudspeaker. With a new, higher-performance 10 inch driver in a larger enclosure, the updated Mk2 version's increased output capability improves its performance not only as a balancing subwoofer but as a more capable stand-alone subwoofer. It also completes the full-bandwidth of the P610 Mk2 when used as the three-way speaker's biamplified woofer element in combination with the P6 Mk2 upgrade.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal
Frequency Response	
-3dB	26Hz
Maximum SPL @ 50Hz	
Continuous	109dB
Peak	115dB
Components	10 inch long-throw driver with 65mm voice coil, 35 liter sealed box
Power Handling	
Continuous	400W
Peak	1,000W
Sensitivity	
1W/1m	94dB
Connectivity	Gold plated binding posts
Construction	Void free MDF internally cross braced

Dimensions	18.1" x 18.9" x 8.6"
WxHxD	460 x 480 x 220 mm (rubber feet +12mm)
Shipping Carton	23.6" x 23.6" x 13.8"
WxHxD	600 x 600 x 350 mm
Net Weight	55.1 Lbs / 25 Kg
Shipping Weight	59.52 Lbs / 27 Kg
Included	Damper feet
Assembly	Belgium; 100% QC testing
Amplification	External amplifier is required
Recommended Amplifier	1-ch DA03-DSP

Procella Amplifiers are sold and packaged separately DA03-DSP and DA08-DSP amplifiers include DSP presets for the P610 Mk2 and P10Si Mk2

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio