P15 - SUBWOOFER

SOUND PROCELLA PERFECTED

Dual 15 Inch Passive Subwoofer





INTRODUCTION

In an astonishingly compact enclosure (just 8.75" / 222mm deep), the P15 subwoofer brings the authority and impact of the mighty P18 to medium and small rooms where nothing less than the best bass quality will do. Its dual 15-inch long-throw Italian pro audio subwoofer drivers have 3" voice coils and are mounted in a sealed-box heavily-braced enclosure. The P15 is driven by external amplification with DSP. The P15 blends lightning-quick transient response with massive impact. Capable of 125dB output and able to reproduced bass frequencies in-room flat to 22Hz and below, the P15 is the ideal low-frequency source for mid-sized domestic and professional environments.

TECHNICAL SPECIFICATIONS

Impedance	Each driver is 8 ohms nominal
Frequency Response	
-3dB	22Hz
Maximum SPL @ 50Hz	
Continuous	119dB
Peak	125dB
Components	Dual long-throw pro audio drivers with cast aluminum chassis and ferrite magnets in 75l sealed box.
Power Handling	
Continuous	2 x 800W
Peak	2 x 1,600W
Sensitivity	
1W/1m	97dB
Connectivity	Dual gold plated binding posts. One input per driver
Construction	Heavily internally braced MDF, Black painted finish

Dimensions	22.4" x 36.6" x 8.75"
WxHxD	570 x 930 x 222 mm
Shipping Carton	27.2" x 42.5" x 15"
WxHxD	690 x 1080 x 380 mm
Net Weight	92 Lbs / 41.7 Kg
Shipping Weight	105 Lbs / 47.7 Kg (plus pallet)
Included	Damper feet, parallel input cables
Assembly	Belgium; 100% QC testing
Recommended Amplifier	1-ch DA03-DSP or 1-ch DA08-DSP*

* depending on the roomsize / listening position in combination with the desired SPL

Procella amplifiers are sold and packaged separately.

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio