P18SI - SUBWOOFER

SOUND PROCELLA PERFECTED

Single 18 Inch Passive Subwoofer





INTRODUCTION

Today's highest-performing systems are designed with multiple subwoofers, and the single 18 inch P18Si recognizes the need for a more compact enclosure that builds on the classic P18 reference subwoofer, delivering the same performance with less output by using the same design and driver. In fact, the P18Si is exactly one half of the size of the P18, with its smaller enclosure remaining less than a foot in depth! (11.0" / 280mm). Capable of 127 dB output at 50Hz (133 dB peak), the P18Si is now the subwoofer of choice in systems requiring smaller enclosures, especially when multiple subwoofers are specified and two, three, or four dual-driver P15s or P18s may be too large and/or too costly.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal
Frequency Response	
-3dB	21Hz
Maximum SPL @ 50Hz	
Continuous	127dB
Peak	133dB
Components	Aluminum demodulation ring and Neodymium magnets in 102 liter sealed box
Power Handling	
Continuous	1 x 1,200W
Peak	1 x 3,000W
Sensitivity	
1m/1W	96dB
Connectivity	Gold plated binding posts
Construction	Heavily internally braced MDF Semi-matte textured black paint finish

Dimensions	26.4" x 20.6" x 11.0"
HxWxD	670 x 525 x 280 mm (rubber feet +12mm, grille +10mm depth)
Shipping Carton	31.5" x 23.6" x 15.75"
HxWxD	800 x 600 x 400 mm
Net Weight	66 Lbs / 30 Kg
Shipping Weight	71 Lbs / 32 Kg (plus pallet)
Included	Damper feet
Assembly	Belgium; 100% QC testing
Amplification	External amplifier is required
Recommended	1-ch DA08-DSP

Procella Amplifiers are sold and packaged separately
DA03-DSP and DA08-DSP amplifiers include DSP presets for the P610 Mk2 and P10Si Mk2

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio