U12 - SUBWOOFER

SOUND PROCELLA PERFECTED

Single 12 Inch Passive Subwoofer





INTRODUCTION

Part of the new UNO Series, the U12 introduces a refined approach to low-frequency performance. Built for precision, control, and seamless integration across a wide range of systems. Equipped with a 12" long-throw driver in a sealed enclosure, it delivers fast, accurate bass down to 25Hz. No excess, no boom, just clean, controlled low-end that stays true to the content. Compact in size but capable in output, the U12 is designed to scale effortlessly, whether in smaller rooms or as part of a larger multi-sub setup.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal
Frequency Response	
-3dB	25Hz
Maximum SPL @ 50Hz	
Continuous	108dB
Peak	114dB
Components	12 inch long-throw driver with 75mm voice coil in a 30 liter sealed box
Power Handling	
Continuous	450W
Peak	900W
Sensitivity	
1W/1m	90.5dB
Connectivity	Gold plated binding posts
Construction	Void free MDF, internally cross-braced, painted black finish

Dimensions	
WxHxD	450x504x191mm (+10 grille)
Shipping Carton	
WxHxD	528x588x278mm
Net Weight	19 Kg
Shipping Weight	22 Kg
Included	Damper Feet
Assembly	Belgium; 100% QC tested
Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended

Procella Amplifiers are sold and packaged separately

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio