U18 - SUBWOOFER

SOUND PROCELLA PERFECTED

Single 18 Inch Passive Subwoofer





INTRODUCTION

Part of the new UNO Series, the U18 is built for maximum output, extension, and control in demanding environments. Driven by an 18" long-throw driver in a sealed enclosure, it reaches down to 21Hz with authority, delivering deep, physical bass while maintaining precision and speed. High SPL capability ensures consistent performance, even in large rooms or high-impact cinema systems. Designed for scale, the U18 anchors larger setups with effortless low-end, whether used as a single unit or in multi-sub configurations. Power, control, and clarity, without compromise.

TECHNICAL SPECIFICATIONS

Impedance	8 Ohms nominal
Frequency Response	
-3dB	21Hz
Maximum SPL @ 50Hz	
Continuous	127dB
Peak	133dB
Components	18 inch long-throw driver with 100mm voice coil in a 75 liter sealed box
Power Handling	
Continuous	1200W
Peak	2400W
Sensitivity	
1W/1m	96dB
Connectivity	Gold plated binding posts
Construction	Void free MDF, internally cross-braced, painted black finish

Dimensions	
WxHxD	592x681x246(+10 grille)mm
Shipping Carton	
WxHxD	765x340x642mm
Net Weight	33 Kg
Shipping Weight	36 Kg
Included	Damper Feet
Assembly	Belgium; 100% QC tested
Amplification	External amplifier is required 1ch DA03-DSP / 1ch DA08-DSP recommended

Procella Amplifiers are sold and packaged separately

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio