P8 - LOUDSPEAKER

SOUND PROCELLA PERFECTED

Main, Surround & Height Channels

INTRODUCTION

The P8 sets the tone for what comes next. A refined design approach that defines the next generation of Procella loud-speakers. Built around an all-new 8” driver and a 1.7” compression driver on a patent-pending constant directivity waveguide, it delivers precise dispersion, high output, and consistent performance across the listening area. Clean, controlled, and reliable at any level. With its rigid, internally braced enclosure and improved acoustic design, the P8 maintains clarity and impact without coloration. Whether used as a main, surround, or height channel, it integrates seamlessly within the Procella ecosystem.





TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal
Power Handling	
Continuous	200W
Peak	400W
Frequency Response	
-3dB	70Hz
Maximum SPL	
Freestanding	118dB continuous / 124dB peak
In wall	124dB continuous / 130dB peak
Dispersion Pattern	Constant directivity;
-6dB	20° up, 30° down, 86° H from 1.2kHz
Sensitivity	
1m/1W	91.3dB
Construction	Void free MDF, internally cross-braced, painted black finish

Components	
Midrange	8” driver with 50mm voice coil
High Frequency	1.7” driver on patent pending constant directivity waveguide
Connectivity	Gold plated binding posts, VESA mount
Included	Damper feet, wall bracket
Dimensions	
WxHxD	400x390x178mm
Shipping Carton	
WxHxD	250x466x486mm
Net Weight	13 Kg
Shipping Weight	14.5 Kg
Recommended Amplifier	External amplifier is required 1ch DA03-DSP recommended Sold and packaged separately
Assembly	Belgium; 100% QC testing

Specifications subject to change. | ©2026 Procella Audio Belgium, BV | Procella Audio USA, LLC. | All rights reserved. | www.procella.audio