



Siliconized Elastomeric Roof Coating

RV Shield Siliconized Elastomeric Roof Coating provides a durable, waterproof, and UV-resistant barrier for long-lasting performance. Its strong adhesion and bright white finish make it ideal for RV service technicians and DIY enthusiasts alike. Protect your investment with a reliable, easy-to-use solution.

BUILT FOR PROFESSIONALS, PERFECT FOR DIYERS

- **Two-Coat Application:** Apply two coats for optimal protection.
- **Energy-Saving Finish:** The highly reflective white finish reduces heat buildup inside the RV, maintaining a cooler, more comfortable interior and improving energy efficiency.
- **Strong Adhesion:** Engineered to bond securely with TPO and EPDM single-ply roofing membranes, ensuring dependable protection in varying conditions.
- **Long-Lasting Durability:** Provides a tough, weatherproof shield that stands up to environmental stress, keeping the roof secure for years to come.
- **DIY-Friendly Application:** The water-based formula allows for simple application with a brush or roller and easy cleanup with just soap and water.
- **Reliable Performance:** A trusted solution that ensures a professional-grade finish, giving you confidence that the job is done right.



FOLLOW US ON SOCIALS @GORVSHIELD





TECHNICAL DETAILS

- **Application Temperature:** Apply only when air, surface, and material temperatures are between 50°F and 110°F.
- **Dry Time:** Allow 24 hours to recoat and 24 hours for return to service. The product cures using moisture from the air.
- **Cleanup:** Easily clean tools and spills with soap and water.

COMPREHENSIVE PROTECTION: THE TOTAL RV SHIELD SYSTEM

CLEAN

- Start with a clean, dry surface. Use RV Shield Roof Cleaner and a stiff bristle brush to scrub away dirt and tightly adhered debris.
- Rinse the roof thoroughly with fresh water and allow it to dry completely.

SEAL

- Apply RV Shield SSL Lap Sealant around all penetrations and to termination strips.
- Use RV Shield Repair Tape to address all membrane seams and any damaged areas, creating a secure base for the coating.

PROTECT

- Thoroughly mix the material for 1-2 minutes using a drill and jiffler mixer.
- Apply the first coat at a rate of 1 gallon per 100 sq. ft. Allow 24 hours to recoat.
- Apply a second coat at the same rate for a total application of 2 gallons per 100 sq. ft.

COMPLETE THE SYSTEM WITH COMPANION PRODUCTS

- **RV Shield Roof Cleaner:** Ensures a clean, prepped surface for optimal adhesion.
- **RV Shield Repair Tape:** Provides quick and reliable repairs for seams and tears.
- **RV Shield SIL Lap Sealant:** A UV-stable polyurethane sealant for horizontal surfaces.

A COMMITMENT TO QUALITY

RV Shield products are engineered for superior performance and backed by a guarantee against defects in formulation or manufacturing. When installed by an RV Shield Certified Installer, our system offers customers enhanced warranty options for complete confidence on the road ahead.

QUESTIONS? CALL 1-888-850-5265 OR VISIT GORVSHIELD.COM