



# Silicone Roof Coating

RV Shield Silicone Roof Coating creates a durable, watertight barrier with superior weather and UV resistance. This easy, one-coat solution is perfect for protecting your RV from the elements. Whether you're a pro or a DIYer, it ensures a leak-free roof and lasting peace of mind.

## FOR THE PROFESSIONAL & THE DIY ENTHUSIAST

- **One-Coat Application:** Save time and labor with a single, efficient application process. Get your clients or your own RV back on the road faster.
- **Strong and Flexible:** Creates a durable seal that withstands extreme temperatures and road vibrations, preventing cracks and leaks at critical points.
- **Highly Reflective Finish:** The bright white, cool-roof-rated finish reflects sunlight, reducing heat buildup and keeping the RV interior cooler and more comfortable.
- **Fast-Curing Formula:** Becomes rain-ready in as few as 15 minutes, minimizing downtime and protecting your work from unexpected weather changes.
- **Superior Adhesion:** Bonds directly to TPO and EPDM single-ply roofing membranes, creating a seamless and reliable protective layer.
- **Lasting Performance:** Delivers long-term savings and worry-free adventures with unmatched durability and protection.



**FOLLOW US ON SOCIALS @GORVSHIELD**





## TECHNICAL DETAILS

- **Application Temperature:** Apply when air, surface, and material temperatures are between 50°F and 110°F.
- **Dry Time:** Product cures with airborne moisture. High humidity will accelerate cure time. Allow 24 hours for return to service.
- **Cleanup:** Use mineral spirits for tools and spills.

## COMPREHENSIVE PROTECTION: THE TOTAL RV SHIELD SYSTEM

### CLEAN

- Clean the roof surface thoroughly with RV Shield Roof Cleaner, using a stiff bristle brush to remove all dirt and debris.
- Rinse the entire surface with fresh water and allow it to dry completely.

### SEAL

- Detail all penetrations (vents, skylights) with RV Shield SSL Lap Sealant.
- Reinforce all membrane seams and damaged areas with RV Shield Repair Tape for a secure, watertight foundation.

### PROTECT

- Using a drill and jiffler mixer, mix the material for 1-2 minutes.
- Apply RV Shield Silicone Roof Coating with a brush or roller at a rate of 1.5 gallons per 100 sq. ft. for a seamless finish.

## COMPLETE THE SYSTEM WITH COMPANION PRODUCTS

- **RV Shield Roof Cleaner:** Prepares the surface for maximum adhesion.
- **RV Shield Repair Tape:** Instantly repairs tears and reinforces seams.
- **RV Shield SIL Lap Sealant:** A non-sag, flexible sealant for vents and terminations.

## COMPLETE THE SYSTEM WITH COMPANION PRODUCTS

A fully transferable, lifetime limited warranty is available for purchase through RV Shield Certified Installers when a comprehensive restoration is completed. This manufacturer-backed warranty gives you and your customers confidence in the installation and the products used.

**QUESTIONS? CALL 1-888-850-5265 OR VISIT GORVSHIELD.COM**