

Technical Specifications

Sunray ExcluDoor® 4

Non Fire rated

Technical Specifications

Excludoor® 4

Non Fire rated

Product Range Summary:

A comprehensive range of premium quality, security rated, steel hinged pedestrian doorsets.

- Configurations: Single doorset, equal leaf double doorset and un-equal leaf double doorset options.
- Orientation: Single swing open out.
- Door leaves 45mm thick. Manufactured from 1.5mm thick zinc coated mild steel. (Zintec).
- Door frames manufactured from 1.5mm thick zinc coated mild steel. (Zintec). Single rebate profile as standard. Other profiles available on request.
- Loss Prevention Standard LPS 1175 Issue 7 Security Rating SR4.
- Secured by Design accredited.
- External doors CE/UKCA marked in accordance with harmonised standard BS EN 14351-1.
- Available with weather/draught resistant seals and threshold options.
- Vision panel, door viewer and louvre vent options.

Door Leaf Construction:

- 45mm thick. Manufactured from 1.5mm thick zinc coated mild steel (Zintec) for enhanced corrosion resistance.
- Fully enclosed pop-riveted and welded twin tray construction. Internally reinforced with proprietary materials to suit specified intruder resistance and hardware requirements.
- Minimum of 3 off stainless steel ball bearing butt hinges per leaf.
- Separate hinge bolts incorporated as standard for increased security resistance.
- Door leaves infilled with proprietary core materials to provide an attack resistant, flat, warp and distortion free panel.
- Leading edge of single door leaf provided with external zinc coated steel anti-pry strip which overlaps frame and protects lock bolt. Double doorset incorporates both external and internal anti-pry strips at meeting stiles for additional security.
- All hardware preparations pre-threaded for fasteners and suitably reinforced as appropriate.

Technical Specifications

Excludoor® 4

Non Fire rated

Frame Construction:

- Standard frame profile: Single rebate 100mm x 45mm overall. Double rebate profiles and other sizes available on request.
- Manufactured from 1.5mm thick zinc coated mild steel (Zintec) for enhanced corrosion resistance.
- Butt welded frame joints.
- Factory prepared hinge and strike plate mounting plates.
- Weather/draught seal: Silicone self-adhesive tear drop gasket. Colour: black.

Threshold Options:

Standard threshold: Steel low level with stop. Clear threshold option and alternative thresholds including Approved Document M compliant designs available on request.

Vision Panels:

- Rectangular shaped vision panels to suit application. Clear vision size: 200mm wide x 300mm high.
- Glass specification: Glazing units tested and certified in accordance with Loss Prevention Standard LPS 1270: Issue 1.1
- Method of fixing in accordance with manufacturer's instructions.
- Alternative door viewer option.

Louvre vents:

- Square shaped heavy duty louvre vents to suit application. Clear vent size: 400mm wide x 400mm high approx.
- Louvre blade specification: Hardened steel louvre blades welded in position.
- Anti-vermin mesh available on request.
- Free area excluding vermin mesh: 46.4%.
- Method of fixing in accordance with manufacturer's instructions.

Technical Specifications

Excludoor® 4

Non Fire rated

Fixing Method:

- 2nd fix between structural reveals with steel shims and expansion type anchors. Gap sealed with manufacturer approved mastic sealant.
- Frame fixing holes infilled with snap-fit low profile hole plugs. Colour: black.

Security Rating:

- Tested and certified to Loss Prevention Standard LPS 1175 Issue 7 Security Rating SR4. Certificate No. 234d Part 4.
- Secured by Design accredited.

Thermal Rating:

- Thermal transmittance certified in accordance with BR 497 and BS EN ISO 10211 by BRE.
- U-value for plain single and double doorsets: 2.8 W/m².K
- U-value for single and double double doorsets with vision panels: 3.3 W/m².K

Technical Specifications

Excludoor® 4

Non Fire rated

Hardware:

- Heavy duty stainless steel ball bearing butt hinges. Certified to Class 13 in accordance with BS EN 1935.
- ASSA ABLOY Kaye HS100 Series single and three-point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- Surelock McGill Stirling range single point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- Surelock McGill Purbrook range single point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- Surelock McGill Slimline range multi-point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- MICO Abryll range single point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- MICO INT (942) range multi-point surface mounted locks, including access controlled versions, conforming to BS EN 1125 and BS EN 179.
- Sunray surface mounted barrel bolts.
- Dorma TS 83 overhead door closers with backcheck facility. Conforming to BS EN 1154.
- Zero Z304 door selectors tested to BS EN 1158.
- Hardware factory fitted as standard.

Finishes:

- Top coat: Architectural grade polyester powder coat. 30% gloss level. 60-80 microns thickness.
- Optional primer for enhanced corrosion resistance: Marine grade corrosion resistant zinc rich primer. 60-80 microns thickness.
- Standard stock colour range of 58 colours, 30% gloss level. Other colours and finishes available on request at additional cost and with longer lead times.


For further information or questions about installation of this product contact our installation team:

01233 656648



Access this document on your device

Scan the QR code on the left using a phone or tablet to access the digital version of this document.



Contact Information:

Sunray Doors

An Assa Abloy Group Company
Sunray Engineering Ltd
Kingsnorth Industrial Estate
Wotton Road, Ashford
Kent TN23 6LL

+44 (0)1233 639039
sales@sunraydoors.co.uk
www.sunraydoors.co.uk