

DATASHEET NOMIA 12V160Ah

The Nomia 12V160Ah is a Lithium Iron Phosphate rechargeable battery with a rated capacity of 160Ah. The unique combination of state-of-the-art technology and smart software makes this lithium battery a robust, safe and easy to use energy storage solution.

Compared to conventional lead-acid batteries, the Nomia 12V160Ah lithium battery offers an enormous weight and space saving. It is very efficient, has extremely high performances and is maintenance free.

FEATURES

- Traction battery
- Lithium Iron Phosphate (LiFePO₄): safe lithium technology
- Integrated BMS (Battery-Management system); external interruption device needed
- Glass fiber reinforced plastic (GFRP) Casing, Aluminum / PE sandwich side panels
- Terminals for 2 x M8 Bolts
- Integrated fuse, 32V / 500A
- Wired communication interface: CANopen
- Battery monitoring / History Storage
- Adaptive cell balancing
- Configurable in serial or parallel connection
- Output for bi-stable relay / latching relay



SAFETY

Super B batteries are based on Lithium Iron Phosphate technology (LiFePO₄). This technology offers high thermal stability. On top of that our bespoke casing and electronics further increase safety and durability.

PERFORMANCE



Low maintenance



Fast Charging



High thermal stability



High discharge rates



High capacity



Low weight



High cycle count



Low self-discharge

3-YEAR WARRANTY

Super B's 3-year warranty offers the best peace of mind. It is the benefit of years of continuous engineering improvement and proven experience with all of our batteries in the harshest environments.



ELECTRICAL SPECIFICATIONS

Nominal Capacity	160Ah
Energy	2048Wh
Nominal Voltage	12.8V
Open Circuit Voltage	13.2V
Self Discharge	<3% per Month
Cycle life	>2000 (at 1C charge/discharge, 100% DoD)

CHARGE & DISCHARGE SPECIFICATIONS

Charge Method	CCCV
Charge Voltage	14.3V - 14.6V
Max Charge Current	160A
End of Discharge Voltage	8V
Discharge Current Continuous	480A
Discharge Pulse Current (10 sec)	800A

COMPLIANCE SPECIFICATIONS

Certifications	CE, FCC, UN 38.3, UN ECE R10.05, EN/IEC 62620
Shipping Classification	UN 3480

MECHANICAL SPECIFICATIONS

Dimensions (LxWxH)	417 x 227 x 314 mm 16.4" x 8.9" x 12.4"
Weight	26.9 kg / 59.3 lbs
Case Material	GFRP
Ingress Protection	IP50
Cell Type / Chemistry	Prismatic - LiFePO4

TEMPERATURE SPECIFICATIONS

Charge Temperature	0°C to 45°C ² 32°F to 113°F ²
Discharge Temperature	-10°C to 55°C 14°F to 131°F
Storage Temperature	-20°C to 45°C -4°F to 113°F

GENERAL PRODUCT SPECIFICATIONS

EAN-13	8718531360570
Battery Designation	IFpP/85/170/245/[4S]M/-20 +55/90

¹When temperature is < 0°C / 32°F or > 45°C / 113°F performance will be degraded.