

I'm human



Baby trend hybrid 3 in 1 manual

Reviews on baby trend hybrid 3 in 1. Baby trend hybrid 3 in 1 expiration date. Baby trend hybrid 3 in 1 booster seat manual. Baby trend hybrid 3 in 1 assembly. Baby trend hybrid 3 in 1 manual pdf. Baby trend hybrid 3 in 1 booster car seat blue manual. Baby trend hybrid manual. Baby trend hybrid lx 3-in-1 manual.

WARNING: Always read and understand all instructions and warnings in this manual before using the Car Seat. Failing to do so can increase the risk of SERIOUS INJURY or DEATH in a sudden stop or crash. Store this manual in the pocket provided on the side of the car seat base for future reference. Table of Contents: 1.0 General Warnings and Information 2.0 WARNINGS 3.0 Features and Benefits: * Toddler Car Seat (WITH Built-in Harness System) * High-back Booster Car Seat (WITHOUT Harness System) 4.1 Preparing Car Seat for Use: Assemble the Back Support (see "Assembly and Removal of Back Support" section) before using your Car Seat in your vehicle. 5.0 Proper Use Check List: * ✓ Car seat is securely installed in vehicle. * ✓ The correct belt routing for installation is used based on use of tether. * ✓ Top Tether is used, when possible. * ✓ Harness straps are in harness slots at or above child's shoulders. * ✓ Harness is snugly adjusted around child. * ✓ Discontinue use of Body Insert when child's shoulders are at or above top strap slots. 5.0 Weight and Height Recommendations TODDLER CAR SEAT USE (WITH Built-in Harness System) Child MUST meet all of the following requirements to use Toddler Car Seat mode: 5.0 Weight and Height Recommendations HIGH-BACK BOOSTER CAR SEAT USE (WITHOUT Built-in Harness System) Child MUST meet all of the following requirements to use High-back Booster Car Seat mode: • Child's weight is between 30 and 100 lbs. (13.5.0 Weight and Height Recommendations BACKLESS BOOSTER CAR SEAT USE (WITHOUT Built-in Harness System) Child MUST meet all of the following requirements to use Backless Booster Car Seat mode: • Child's weight is between 40 and 100 lbs. (18 and 45 kg) and • Child's height is between 42 and 57 in. (107 and 145 cm) and • Top of child's ears must be below top of vehicle seat back or vehicle headrest and • Child must be at least 4 years of age. 7.0 Toddler Car Seat (With Built-in Harness) Installation and Use: Locked: For vehicles with switchable retractors, pull the shoulder belt all the way out to switch the retractor into the locking retractor mode and release the shoulder belt allowing it to retract. Installation - Lap Belt Only WITHOUT Top Tether WARNING! • The vehicle seat belt system must stay tightly adjusted to the car seat at all times. If not, read the vehicle owner's manual and "Vehicle Seat Belts" section in this manual. To secure the car seat in the vehicle: 1. Assemble the Back Support (see "Assembly and Removal of Back Support" section). 2. Check for a secure installation by grasping the car seat armrest and pushing side-to-side and front-to-back. The car seat should not move more than 1 inch in either direction. • If the car seat moves more than 1 inch, retighten the LATCH belt and test again. WARNING! DEATH or SERIOUS INJURY can occur: • Failure to properly adjust the harness on your child increases the risk of death or serious injury in the event of a sudden stop or crash. Follow the instructions very closely to ensure that the harness is properly adjusted to fit your child at all times. Your child will grow rapidly! Please check the fit of the harness every time you use the Car Seat. 4. Snugly adjust the harness around your child by pulling the harness adjuster strap at the front of the car seat shown. 5. Close Harness Clip and position as close to armpit level as possible. 6. Check that the Harness Straps are snugly adjusted. 8.0 To remove your child: 1. Unbuckle Harness Clip – press on the tabs in the top and bottom of the Harness Clip 1 and pull apart 2 to open the Harness Clip. 2. Unbuckle the Harness Buckle to open the Harness System. 3. Slide the Harness straps off the child's shoulders and arms. 4. Remove your child. 8.0 Booster Car Seat (Without Built-in Harness) Installation and Use WARNING! DEATH or SERIOUS INJURY can occur: • If the child will not keep the vehicle shoulder belt properly positioned on their shoulder, DO NOT use this Booster Car Seat. Use a different child restraint system. Do not allow the child to slide down in the High-back Booster Car Seat which could position the vehicle lap belt across the child's abdomen and shoulder belt over their neck or face. Do not use Body Insert in Booster use mode. 5. If the vehicle seat back is adjustable, adjust into the upright position or the position specified in the vehicle owner's manual Inner for use with a car seat. 6. Thread the shoulder belt into the inner slot of the Booster Shoulder Belt Guide located on the Retainer underside of the Head Support. Tab - Slide the shoulder belt into the open end of the slot, around the Belt Retainer Tab and into Inner Slot of the Head Support. To ensure proper installation and use of the booster car seat, follow these guidelines: 1. Place the vehicle lap belt across the front of the child and buckle it securely. 2. Assemble the vehicle shoulder belt positioner to the back of the car seat, following the instructions in the manual for assembly and removal. 3. Check that the vehicle seat belts fit the child correctly: the lap belt should be low on the hips, contacting the thighs, while the shoulder belt should contact the chest and be centered on the shoulder. 4. Do not place the vehicle shoulder belt under the child's arm or behind the child. 5. Use the back support as long as possible to ensure maximum safety. 6. When using a combination lap/shoulder belt with retractor, follow the specific instructions provided by your vehicle's owner's manual and ensure that all requirements are met. The harness straps on your car seat should be adjusted to four different heights so that they're at or just above your child's shoulders. If their shoulders are between two levels, always use the higher one. Remove the body insert if their shoulders go above the highest set of harness slots. To adjust the harness strap height, take off the straps from the back support, move them to a spot at or just above the child's shoulder, and reattach them. When removing the harness, unbuckle it and loosen the straps by pressing the Harness Adjuster and pulling out on the straps. To assemble the harness, place the buckle facing down into the seat and secure it with the Crotch Belt. Make sure the harness straps are at or above the child's shoulders to avoid serious injury in case of a sudden stop or crash. The Head Support can be moved up or down through different positions but should never be removed from the Back Support. To attach the Shoulder Belt Positioner, lay it flat and insert the vehicle shoulder belt into both sides of the clip. This car seat conforms to all Federal Motor Vehicle Safety Standards for use in motor vehicles and aircraft. However, it's not certified for use in aircraft without the harness system. When cleaning or maintaining your car seat, avoid using it without the seat, back support, and head support pads. To remove these parts, slide out the elastic loops from the inner shoulder belt slot, pull off the pad, and unhook it from the top of the back support. Given article text here www.babytrend.com Please complete the following information. The model number and manufactured in (date) can be found on a label on the bottom of the child restraint. Page 21.0 General Warnings and Information 3. WARNING TO PARENTS AND CAREGIVERS Proper use is required! Even if using this car seat seems easy to figure out, it is very important to follow the car seat and vehicle owner's manuals! Failure to follow these instructions and Car Seat labels can result in a child striking the vehicle's interior during a sudden stop or crash. Your child's safety depends on proper installation and use of this car seat. Read and understand all information in this owner's manual and product labels before using this car seat. Improper use of the car seat can result in serious injury or death from a sudden stop or crash. The ultimate safety of your child depends on the proper and secure installation of the Car Seat in your vehicle. Proper installation requires that you read and understand this entire manual and your vehicle's owner's manual before placing your child in the seat. DO NOT allow others to install or use this Car Seat unless they completely understand its proper installation and use. Your child's safety depends on: 1. Choosing the correct use mode for your child's weight and height. 2. Choosing the best location within your vehicle for installing the Car Seat. Seating positions with frontal Air Bags must be avoided if possible. 3. Proper installation. a. Toddler Use Mode - Requires proper routing of LATCH or the vehicle seat belts and using Top Tether. Use Top Tether as an additional attachment to secure Car Seat whenever possible. 4. Car Seat must stay tightly secured in vehicle. b. Booster Use Mode Requires proper routing and adjusting of vehicle lap/shoulder belt. c. Always properly position the vehicle belts on your child and snugly adjust the vehicle belts around child. NOTE: Not all vehicle seat belts or vehicle seats can be used with this car seat. 4. Proper belt adjustment. - Properly position belt on child. - Snugly adjust belts around child. No car seat can guarantee protection from injury in every situation, but proper use helps reduce the risk of serious injury or death. NEED HELP? Contact Baby Trend Customer Service Department at 1-800-328-7363 with any questions concerning your car seat. Please have the model number and manufactured in (date) on your car seat available when calling or contact one of the following resources: • Call 1-866-SEATCHECK(1-866-732-8243). • Log onto www.nhtsa.gov - For a car seat inspection station select "Locate a Child Safety Seat Inspection Station By State or Zip Code". • Log onto www.seatcheck.org. 1.0 General Warnings and Information Page 31.0 General Warnings and Information..... 32.0 WARNINGS..... 53.0 Features and Benefits 3.1 Toddler Car Seat..... 9 3.2 Toddler Car Table of Contents for Car Seat Installation and Use Section 1: Booster Car Seats * High-back booster car seat: page 11 * Backless booster car seat: page 12 Section 2: Preparing the Car Seat * Assemble back support: page 13 * Determine use mode and prepare car seat: pages 13-14 * Select vehicle seating location: pages 14-15 Section 3: Weight and Height Recommendations * Car seat use modes: page 16 * Toddler car seat use: page 17 * High-back booster car seat use: page 18 * Backless booster car seat use: page 19 Section 4: Selecting a Vehicle Seating Location * Overall considerations: pages 20-21 * Seating locations to avoid: page 23 Section 5: Toddler Car Seat Installation and Use * Proper installation: page 24 * Belt routing options: pages 26-27 Section 6: Booster Car Seat Installation and Use * High-back booster car seat installation: page 59 * Backless booster car seat installation: page 65 Section 7: Vehicle Seat Belts * Checking vehicle seat belt safety: page 68 Section 8: Operation and Adjustments * Assembly and removal of back support: page 75 * Changing harness strap adjustment: page 76 * Harness removal and assembly: page 81 1. Assembly and Removal of Vehicle Shoulder Belt Positioner..... 2. Additional Information..... 3. Certifications..... 4. Installation and Use on Aircraft..... 5. Cleaning and Maintenance..... 6. Replacement Parts..... 7. How to Register your Car Seat..... This child restraint has a label at the bottom with important info. It's got a model number, manufacturing date, and purchase date on it. To stay safe, you gotta register this thing so you can get recalled if needed. Fill out the prepaid postcard that came with the safety harness and send it in ASAP. If you've got questions or need help, call Baby Trend at 1-800-328-7363 or check their website. For recall info, contact the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 or visit www.safercar.gov. Just have your model and manufacturing date ready when you call. They're on a white label at the bottom of the child restraint.