

Description

Compared to dry gauges, liquid-filled gauges provide greater durability, better resistance to temperature changes, and reduced adverse system pressure pulsations and line vibration effects on reading accuracy. You can also expect better moisture resistance with less condensation and icing, along with a longer gauge lifespan for a more dependable part.

Find the right liquid-filled gauge configuration for your operation- and get it with shorter delivery timelines and reduced costs.

Features and Benefits

- Available in 2.5" and 4" Dial
- Bottom mount and back mount configurations
- Fully stainless steel construction
- Pressure ranges from 30 psi to 5000 psi
- Connection size in 1/4" or 1/2" NPT
- Vibration-proof type IP65
- Glycerin filled
- Closed system provides ingress protection



Product Numbering			
Style	Dial Size	Thread Size	Pressure Range
GA	2.5	1/4	30
Standard connection gauge	2.5" dia. dial	1/4" male NPT thread	30 psi
GABM	4	1/2	60
Back mount gauge	4" dia. dial	1/2" male NPT thread	60 psi
			160
			160 psi
			300
			300 psi
			600
			600 psi
			1000
			1000 psi
			1500
			1500 psi
			2000
			2000 psi
			5000
			5000 psi
Example: model number GA-2.5-1/4-1000 is interpreted as, Standard connection gauge, 2.5" diameter dial, 1/4" male NPT connection thread, 1000 psi pressure range.			

