

solc SURFACE

Interior Ambient LED Luminaire

Solo Surface is a semi-direct interior ambient luminaire featuring a modern aesthetic with an incredibly small profile. Paired with a highend diffuser lens that delivers smooth illumination free of dark spots and pixilation, the Solo is the premier architectural luminaire for today's interior spaces.

Client:	
Order#:	
Project:	
Type:	

FEATURES

PERFORMANCE

- Delivers up to 100 lm/W at 4000K
- 70% direct/30% indirect distribution
- Accurate interior color rendering with 90+ CRI
- Voltage: 120-277V (Universal) or Power over Ethernet (PoE)
- R9 value of 60+

PHYSICAL

- Housing: 9/16" x 1.5" extruded T5-6063 Aluminum with a clear anodized finish
- Designed for a remotely-mounted driver with a low-voltage power drop.
- Housing features an internal screw channel for mounting the LED board, 2 internal L channels to slide the lens into the housing, and an external T channel on the top side to slide the mounting hardware.
- For more features see page 2



USA
Buy American
Act Compliant

5Yr
Warranty
(10 optional)

Model Number	CCT	CRI	Projected Lifetime	Dimming	Operating Temperature	Warranty
Interior Ambient LED Luminaire	2700K, 3000K, 3500K, 4000K,	90+	245,000 Hours (L80); 104,000 Hours (L90)	0-10V Dimming Standard	-40°C to +50°C Ambient	5 year Standard
						10 year Optional

ORDERING INFORMATION

SS / LENGTH / OUTPUT / CCT / U / FINISH / MOUNTING PROVISIONS / OPTIONS / WARRANTY

FIXTURE SERIES		CCT	
SS	Solo Surface	27	2700K
LENGTH		30	3000K
2	2'	35	3500K
3	3'	40	4000K
4	4'	VOLTAGE	
6	6'	U	120-277V
8	8'	FINISH	
OUTPUT		W	Matte White (Standard)
L	6.4W/ft	S	Silver
M	9.6W/ft	B	Black
H	12.8W/ft	C	Custom

MOUNTING PROVISIONS	
HL	Hard Lid/Drywall Ceiling
TB	T-Bar Grid Ceiling
WL	Drywall Wall Mount
OPTIONS	
ES1	Lutron LDE1 Series EcoSystem 1% Dimming with Soft On Fade to Black
N	None
WARRANTY	
5	5 Year Warrant
10	10 Year Warrant Optional


¹ ES1 Option only available up to 90W

² 5 Year Warranty is Standard unless specified

Features (continued)


- :: Aluminum Housing With Matte White Finish
- :: Custom Colors Available
- :: Lens Snaps into Housing
- :: Make Different Connections Via L Joints on Both Ends
- :: Mounting Options: Surface, Suspended, Wall
- :: IP Rating: IP54
- :: Operating Temperature
- :: Dimmable: 0~10V Dimming
- :: Total Lumens: 4765M/ 5090LM/ 4967LM/ 5052LM
- :: Color Temperatures: 3000K/3500K/4000K/5000K
- :: Multi-CCT(Selectable Switch Inside Fixture)
- :: Color Rendering Index: CRI ≥ 80
- :: Up Light Option Available
- :: 50,000 Hours Rated Life
- :: 5-Year Warranty

Dimensions



RCC %:	80				70				50			30			10			0
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30	20	0
RCR: 0	1.12	1.12	1.12	1.12	1.06	1.06	1.06	.71	.95	.95	.95	.85	.85	.85	.75	.75	.75	.71
1	.99	.93	.87	.82	.93	.87	.83	.53	.78	.74	.70	.69	.66	.63	.61	.58	.56	.52
2	.88	.79	.71	.64	.83	.74	.67	.42	.66	.60	.55	.58	.54	.50	.51	.48	.44	.41
3	.80	.68	.59	.52	.75	.64	.56	.34	.57	.50	.45	.50	.45	.41	.44	.40	.36	.33
4	.73	.60	.50	.43	.68	.56	.48	.29	.50	.43	.37	.44	.39	.34	.39	.34	.30	.27
5	.66	.53	.43	.36	.62	.50	.41	.24	.45	.37	.32	.39	.34	.29	.35	.30	.26	.23
6	.61	.47	.38	.31	.57	.45	.36	.21	.40	.33	.27	.35	.29	.25	.31	.26	.22	.20
7	.56	.43	.34	.27	.53	.40	.32	.19	.36	.29	.24	.32	.26	.22	.28	.23	.20	.17
8	.52	.39	.30	.24	.49	.37	.29	.17	.33	.26	.21	.29	.24	.19	.26	.21	.17	.15
9	.49	.35	.27	.21	.46	.33	.26	.15	.30	.23	.19	.27	.21	.17	.24	.19	.16	.14
10	.46	.32	.24	.19	.43	.31	.23	.13	.28	.21	.17	.25	.19	.15	.22	.18	.14	.12

Model 4ft Low Output 3500K



Zonal Lumen Summary

Zone	Lumens	%Luminaire
0-30	187.2	13.2%
0-40	314.9	22.3%
0-60	608.8	43.1%
60-90	392.8	27.8%
70-100	344.7	24.4%
90-120	251.6	17.8%
0-90	1,001.6	70.9%
90-180	412.0	29.1%
0-180	1,413.6	100%

Wall Mount

Optionally install the wall mounting bracket on the back of the fixture. The connection cables will enter the fixture through one of these brackets. Please specify the desired wire entry location from the wall on your purchase order



Hard Lit / Drywall Ceiling / T-Bar Grid Ceiling

