

ARTEMIS: Rosha 2"

Architectural Recessed Down Light (Adjustable)

Rosha 2" Spotlights come in adjustable, adjustable tube, and wall washer format. Meeting for your needs, these down lights are made with quality aluminum, granting a Ingress Protection grading of IP 20.

Client:	
Order#:	
Project:	
Type:	

FEATURES

- Cold-forged aluminum radiator, twice heat dissipation of the die-cast aluminum
- COB LED Chip, deep hidden light source, multiple anti-glare
- Aluminum Reflector, Much better lighting distribution than plastic
- Fully metal made, good texture, high performance
- Comes in trim & trimless



PERFORMANCE DATA

Product ID	Body	Apperance	Wattage	Ingress Protection	Beam Angle	CCT	CRI	Driver Voltage & Options
ROSHA-A	Adjustable	Trim & Trimless	Max: 15W	IP20	15° 25° 35° 50°	2700K 3000K 3500K 4000K Dim to Warm 2700-1800K 3000-1800K	90Ra	120-277Vac

ORDERING INFORMATION

ROSHA / A / / / / /
 SERIES BODY APPEARANCE REFLECTOR COLOR CCT BEAM ANGLE WARRANTY

FIXTURE SERIES	
ROSHA	Rosha 2" Recessed Deco Downlight
BODY	
A	Adjustable
APPEARANCE	
T	Trim
TL	Trimless
REFLECTOR COLOR	
W	White
B	Black

CCT	
27K	2700K
30K	3000K
35K	3500K
40K	4000K
WD18/27K	Warm Dim 1800K to 2700K
WD18/30K	Warm Dim 1800K to 3000K
BEAM ANGLE	
15	15°
25	25°
35	35°
50	50°
WARRANTY	
5	5 Year Warranty (included)
10	10 Year Warranty



ROSHA-A-T



P. system	I (led)	Beam Angle	CCT	Lumens
15W	350mA	15°	2700K	762.0 lm
			3000K	814.5 lm
			4000K	925.0 lm
15W	350mA	25°	2700K	1145.3 lm
			3000K	1197.8 lm
			4000K	1308.3 lm
15W	350mA	35°	2700K	1239.3 lm
			3000K	1291.8 lm
			4000K	1402.3 lm
15W	350mA	50°	2700K	1331.7 lm
			3000K	1384.2 lm
			4000K	1494.7 lm



Light Source	Input Voltage	CRI	UGR	Shielding Angle
LED COB	DC36V	90Ra	☒ 13	50°



With Trim



White



Black

Driver: 120-277Vac ON-OFF | TRIAC | 0/1-10V | DALI

ROSHA-A-TL



P.system	I (led)	Beam Angle	CCT	Lumens
15W	350mA	15°	2700K	762.0 lm
			3000K	814.5 lm
			4000K	925.0 lm
15W	350mA	25°	2700K	1145.3 lm
			3000K	1197.8 lm
			4000K	1308.3 lm
15W	350mA	35°	2700K	1239.3 lm
			3000K	1291.8 lm
			4000K	1402.3 lm
15W	350mA	50°	2700K	1331.7 lm
			3000K	1384.2 lm
			4000K	1494.7 lm


 |  |  |  | 

Light Source	Input Voltage	CRI	UGR	Shielding Angle
LED COB	DC36V	90Ra	≤ 13	50°


 |  |  |  | 

 2" (62mm) |  Aluminum |  Required Remote Driver*

2.17" 55mm



0.98" 25mm



20° 360°

2.17" 55mm

3.15" 80mm | 3.54" 90mm

Trimless

 White

 Black

Driver: 120-277Vac ON-OFF | TRIAC | 0/1-10V | DALI

Accessories

Drivers in Junction Box




CMEM55

Triac

8W/10W/12W/15W

For 1




KIG-DWJ

Triac/0-10V/1-10V


Potentiometer/10V PWM 5 in 1

20W/40W/60W

For 1-6



Brackets for New-Construction




BRKT-3R45A

For Artemis trim & trimless

Type: New construction plate

Cut out:

Round: Ø1"*(Ø50mm)



Remark

Tailored brackets are available with a reasonable surcharge, details as below,

- The customized brackets' dimensions are still the same as the existing ones, 600*200mm
- Hole sizes can be customized within the range of 25-100mm
- Holes quantity can be indicated, 1-7pcs
- Holes' positions on the bracket can be done as requests

Brackets for New-Construction (4-legs)

NCP-SR3-R21

For Artemis trim & trimless








Cut out:

Round: Ø3" (Ø77mm)

Ø2" (Ø62mm)

Ø1" (Ø50mm)

Square: □ 3" (□77mm)



IC-Box for New-Construction (4-legs)

NCBX-SR3-R21

For Artemis trim & trimless








Cut out:

Round: Ø3" (Ø77mm)




Ø2" (Ø62mm)

Ø1" (Ø50mm)

Square: □ 3" (□77mm)



NON-IC Wire Diagram



IC Rated Wire Diagram

