

LUCENT

SURFACE Linear

Lucent is a compact 45° angled profile designed for surface mounting on shelves, cabinetry, or displays. Its 8.1mm LED slot and internal PC diffuser create soft, directional beam control without glare. The aluminum body installs securely via snap-fit clips, offering quick access for maintenance or strip replacement. Ideal for task lighting, accent highlights, or retail shelving where clean edges and uniform output are essential.

Client:	
Order#:	
Project:	
Туре:	

17

SPECIFICATIONS

LED STRIP Fits LED strips up to 8.1mm (0.31 in)

WATTAGE 1.7W

LUMEN OUTPUT 210

LENS Frosted

LENGTH OPTIONS Cut Points: 4 inch

CRI 90+

COLOR TEMPERATURE 27K / 3K / 35K / 4K

DIMMING Dimmable LED Drivers

CONNECTIONS End to End In-Field

RATING IP20
CERTIFICATIONS UL & ETL

-	
DLC	
LISTED	
PREMIUM	





ORDERING INFORMATION

LUCENT	/	//	/	/ ,	/ ,	/ /	/
MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER

MODEL	LENGTH	LIGHT OUTPUT	COLOR TEMP	FINISH	LENS	VOLTAGE	DRIVER
LUCENT	79.2 79.2 in. XX Custom Length	1.7 W 1.7 Watts	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White CC Custom Color	FL Frosted Lens	24 24 Volts	EB TRIAC ELV Dimming D10 0-10V Dimming HL2W Lutron 2-Wire HL3E Lutron ECO 3-Wire

Commerce CA 90040

DIMENSIONS

